



Elongated Floor-Mounted ADA Pressure Assist Water Closet

WETS-8029.8013

Product description

SloanTec® Glaze, Floor-Mounted 1.6 gpf (6 lpf) ADA 12" Rough-in Left Handle Pressure-Assisted Tank Toilet.

Code 87298013

Downloads

- [Pressure-Assisted Toilets Installation Instructions.pdf](#)
- [Flushmate Owner's Manual.pdf](#)
- [Pressure-Assisted Toilets Repair and Maintenance Guide.pdf](#)
- [Pressure-Assisted Toilets Brochure.pdf](#)
- [Fixture Brochure.pdf](#)
- [Additional Downloads](#)

Videos

- [Sloan - Company Overview](#)

Details

- Flush Volume: 1.6 gpf (6 lpf)
- Handle Side: Left

Features

- White Vitreous China
-
- Elongated bowl
-
- Floor mounted, floor outlet
-
- 12" (305mm) rough-in
-
- Chrome metal flush handle
-
- Secure, anti-rocking 3-point tank mounting system
-
- Powered by Flushmate® brand pressure-assist flushing technology to achieve 1,000g MaP score
-
- Over 60 ft (18.3 m) drainline carry performance
-
- Water spot area: 11 ¼ x 9 ¾ (286 mm x 248 mm)
-
- Smooth, quiet cable activated flush handle - left hand
- Fully glazed trapway
-
- Closet bolts and caps included
-
- Toilet seat and wax ring not included
-
- Tank and bowl are packed in a single carton
- ADA compliant

Components

- Bowl: Code 2178029
- Tank: Code 2108013

Warranty

[View Warranty Information](#)

Notes

All information contained within this document subject to change without notice.

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

Static load tested according to the procedure outlined in Section 6.7 of ASME A112.19.2. Not recommended for bariatric use.

WaterSense compliant when used with a WaterSense compliant flushometer.

