

# Warwick Hanger Company

TEL. (401)596-8062

FAX (401)596-8063

34 Canal Street  
Westerly, RI 02891

## 1400 & 1425 Series Plastic J Hook Pipe Hanger Specification Sheet

**Subject:** Plastic Pipe Hangers

**Material:** High impact ABS (Color: White)

**Use:** Used in the installation of ABS, PVC and Copper Pipe for water and drain waste vent.

### Installation Requirements:

#### Horizontal Piping:

**Copper Tube:** Copper tube shall be supported at each story and at not more than 4 feet (1219mm) intervals.

**Plastic Pipe:** Plastic piping shall be supported at each story and at not more than 4 feet (1219mm) intervals.

Drain waste vent pipe shall allow for 1/8" fall per foot (supported every 4 feet).

### Load Specification: Drain Waste Vent Hook Strength

	Total weight per	Safe working load
	Four (4) foot section	(per hanger)
	Of PVC sch. 40 PVC	
Size	Full of water	Pipe Hangers
1 1/2"	5.6 lbs.	40 lbs
2"	8.5 lbs.	40 lbs
3"	18.4 lbs.	40 lbs.
4"	31.4 lbs.	40 lbs.

Hangers safe working temperature of 220 degrees Fahrenheit