



**THE PREMIUM EMERGENCY WINTER
DIESEL FUEL TREATMENT**

MELT DOWN

**WORKS WITH ALL
FUEL SYSTEMS**

- MELT DOWN is a safe unique blend of organic compounds designed to dissolve ice and wax in gelled diesel fuel.
- MELT DOWN reacts within 20 minutes and solubilizes the wax and ice crystals in diesel fuel to completely thaw the fuel in the entire diesel fuel system.
- MELT DOWN is compatible with all types of diesel fuel, biodiesel and home heating oil. Melt Down does not contain chlorinated solvents, methanol, or harmful alcohols that could harm fuel pumps, injectors or other precombustion components.
- MELT DOWN works in all fuel systems including common rail.

MADE IN  THE USA



*Reliquefies
gelled diesel fuel
in 20 minutes*



"FPPF prides itself as the technology leader in the fuel additive business. For over 25 years we have set the standard for quality performance and value. We will continue to provide our customers a superior line of products."

Chris Lory

Chris Lory
Founder



*The Premium
Fuel Additive
Company*

FPPF CHEMICAL COMPANY, INC.
1-800-735-3773

MELT DOWN *Product Data Sheet*



PRODUCT USE

Simply follow label instructions to relieve gelled fuel in your truck or bulk storage tank.

DOSAGE

Add one quart (32 ounces) directly to each 50 gallons of gelled fuel in the tank. Disconnect fuel filter assembly, remove any gelled fuel by adding a 50/50 mix of diesel fuel and Melt Down (usually 3 ounces of each) to the bowl of the fuel filter and reconnect. Wait 20 minutes and restart your vehicle.

HANDLING

Consult product SDS for proper handling, safety, storage, and spill information.

Packaging:

Description	Case count	Stock #	Case weight
32 ounce bottle	12/case	90124	27 lbs.
1 gallon jug	4/case	90330	40 lbs.
55 gallon drum	—	00170	450 lbs.

DISTRIBUTED BY:




FPPF CHEMICAL COMPANY, INC.

117 WEST TUPPER STREET
BUFFALO, NEW YORK 14201
TEL: (716) 856-9607

1-800-735-3773

FAX: (716) 856-0750
E-MAIL: sales@fppf.com
WEBSITE: www.fppf.com



Fm. No. 04010 06/20