

## Features

- 5" (127 mm) gooseneck spout reach.
- Gooseneck spout swivels for unobstructed use of the sink.
- Two lever handles offer separate control of hot and cold water.
- Aerated flow delivers a smooth, steady stream of water.
- 1.5 gpm (5.7 lpm) maximum flow rate at 60 psi (4.14 bar).
- Quarter-turn washerless ceramic disc valves.
- Less drain.

## Material

- Premium metal construction for durability and reliability.
- KOHLER finishes resist corrosion and tarnishing.

## Installation


- For 4" (102 mm) centers.
- Three-hole installation.

## Recommended Products/Accessories

K-23723 Faucet cleaner

## Optional Products/Accessories

1012715



ADA

CSA B651

## Codes/Standards

ASME A112.18.1/CSA B125.1

NSF/ANSI 61

NSF/ANSI 372

All applicable US Federal and State material regulations

DOE - Energy Policy Act 1992

California Energy Commission (CEC)


ADA

ICC/ANSI A117.1

CSA B651

## KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.



**Technical Information**

All product dimensions are nominal.

Drain included: No

**Spout:**

Spout reach: 5" (127 mm)

**Notes**

Install this product according to the installation instructions.

ADA, CSA B651 compliant when installed to the specific requirements of these regulations.