

PC 441-10A-Series

Sump Pump Combo Series

Liberty Pumps®

A Family and Employee Owned Company

Pre-assembled primary pump and battery back-up system

Compact design


Drop-in-the-pit ready

Features

- Provides uninterrupted pumping in the event of power outage or main pump failure
- Fully assembled
- Primary pumps available in 1/3 or 1/2 hp
- Ready to connect to 1-1/2" discharge
- 12-Volt battery operated
- Compact profile will fit minimum 15" diameter and 18" deep sump pits
- System includes separate check valves for both primary and back-up pumps
- Model 441-10A back-up system includes:
 - 10A Battery charger and maintainer, with integrated back-up pump controls
 - Meets US DOE and California CEC energy efficiency standards
 - Self-resetting 24 hour silence
 - Audible and visual alarm warns of back-up pump operation
 - Battery voltage display on charger

Models

PC237-441-10A	1/3 hp (Model 237 and 441-10A)
PC257-441-10A	1/3 hp (Model 257 and 441-10A)
PC457-441-10A	1/2 hp (Model 457 and 441-10A)
PCS37-441-10A	1/3 hp (Model S37 and 441-10A)
PCS37-P-441-10A	1/3 hp (Model S37-P and 441-10A)



Battery not included



innovate. evolve.


PC441-10A-Series

Included in Complete System


- Primary Pump, 115V
- 441-10A Back-up pump, 12 VDC
- 1-1/2" PVC piping with rubber coupler between primary pump and back-up pump (rubber coupler provides easy removal and serviceability of back-up pump)
- Check valve included on primary pump and back-up pump
- Completely assembled
- Maximum fluid temperature 140°F
- Battery not included. 12-Volt marine-type deep cycle battery recommended. (Charger compatible with Group 27 or 31, AGM, Gel, and Wet cell batteries)

For optimum performance, Liberty Pumps StormCell® batteries recommended

Primary Pump Performance Curve




Primary Pump Options



Back-Up Pump Performance Curve

Model 441-10A



Models and Specifications

MODELS	DESCRIPTION	PRIMARY PUMP	BACK-UP PUMP	BATTERY CHARGER	SYSTEM WEIGHT
PC237-441-10A	1/3 hp (Model 237 and 441-10A)	115V, 5.2A	12 VDC	10A	27 lbs
PC257-441-10A	1/3 hp (Model 257 and 441-10A)	115V, 5.2A	12 VDC	10A	39 lbs
PC457-441-10A	1/2 hp (Model 457 and 441-10A)	115V, 7.3A	12 VDC	10A	32 lbs
PCS37-441-10A	1/3 hp (Model S37 and 441-10A)	115V, 6.2A	12 VDC	10A	30 lbs
PCS37-P-441-10A	1/3 hp (Model S37-P and 441-10A)	115V, 6.2A	12 VDC	10A	30 lbs

Minimum pit size for all above systems 15" diameter x 18" depth

For complete primary pump specifications see appropriate 230-Series, 250-Series, 450-Series or S30-Series literature.

For complete back-up pump specifications see Model 441 literature.

Specifications subject to change without notice.

Copyright © Liberty Pumps, Inc. 2021 All rights reserved. LLIT006784-R02/21

Liberty Pumps - 7000 Apple Tree Avenue - Bergen, New York 14416
Phone 800-543-2550 - Fax 585-494-1839 - www.LibertyPumps.com