

### 3450 Combination Boiler Feed Valve & Backflow

The integral design of the Taco 3450 Combi Valve combines a cartridge style backflow preventer with a pressure regulating cartridge style boiler feed valve into a unique one piece body configuration. Taco's 3450 combination dual check backflow with atmospheric vent and boiler feed valve with purge auto-reset, dial in pressure setting and adjustable indicator sets a new standard for performance and serviceability.



# Submittal Data Information 3450 Combination Boiler Feed Valve & Backflow

Submittal Data # 101-168

Effective: 10/01/15

Supersedes: 09/01/15

## Features

- Auto Reset from Fast Fill
- ASSE 1081-2014
- Simple Pressure Adjustment
- Servicable Cartridge for both the Backflow and Feed Valve
- Adjustable 360 View of Pressure Indicator
- Large Adjustment Range
- Servicable without draining the system
- One Piece Body Construction
- Stainless Steel Strainer

## Performance


- Max. Inlet Pressure:.....150 psi (10.3 Bar)
- Min. Delta P Inlet to Outlet...15 psi (1 Bar)
- Recommended Setting Range: 10-50 psi  
+/-3 psi  
(.7-3.4 bar)
- Factory Setting: ..... 12psi (.8)
- Adjustment Capability: .....8.5 - 65 psi  
(.6-4.5 bar)
- Max. Flow Rate:..... 25 gpm  
(8 ft / sec)  
95 l/m
- Max. Temperature:..... 210°F (99°C)

## Materials of Construction

- Body:.....Forged Brass
- Cartridge Components:.....Brass, EPDM,  
Hi-Temp  
Engineered  
Plastics and  
Stainless Steel
- Gaskets:..... EPDM

## Application:

The integral design of the Taco 3450 Combi Valve combines a cartridge style backflow preventer with a cartridge style feed valve into a unique one piece body configuration. Designed for use in hydronic heating systems the dual check backflow prevents heating system water from flowing back into the supply water piping if the supply pressure falls below the heating system pressure. The boiler feed valve automatically fills or refills (make-up water) the closed heating system to the desired cold fill pressure. Both the backflow and the feed valve contain cartridges that can be serviced or replaced without draining the entire heating system.



## Dimensions: (FOR REFERENCE PURPOSES)

Model Number	Description	A		B		C		D	
		in.	in.	mm	in.	mm	in.	mm	
3450	1/2" NPT x 1/2" Union Sweat	1/4 NPT	4-1/2	114.3	3-1/4	82.6	3-1/2	88.9	
3450-T	1/2" NPT x 1/2" Union NPT	1/4 NPT	4-1/2	114.3	3-1/4	82.6	3-1/2	88.9	

