



**Viega ManaBloc access panel**

- Plastic

Note

Can be mounted to open vertically or horizontally

**Model V5099**

W [in]	L [in]	max. Ports	Wt [lb]	Quantity	Part No	DG
14	18	14	1.350	1	<b>50718</b>	2
14	26	16	0.050	1	<b>50726</b>	2
14	30	24	2.434	1	<b>50730</b>	2
14	39	36	3.249	1	<b>50739</b>	2



**Viega ManaBloc access panel**

- Metal

- 3 hour fire rating

components

(2) knurled knobs, (2) keys

Note

Can be mounted to open vertically or horizontally

UL listed

**Model V5099.1**

W [in]	L [in]	max. Ports	Wt [lb]	Quantity	Part No	DG
14	40	30	26.258	1	<b>50740</b>	2

**Manifolds**



**Viega PEX Press manifold**

**Smart Connect feature**

- Only use with lock clip Part No 58075

- Polymer

- Press connection

- Flow through

Note

Does not include mounting hardware

**Model V5636**

Outlet(s)	P1	P2	P3	Wt [lb]	Quantity	Part No	DG
2	3/4	3/4	1/2	0.202	10	<b>49152</b>	6
3	3/4	3/4	1/2	0.255	10	<b>49153</b>	6
4	3/4	3/4	1/2	0.318	10	<b>49054</b>	6
4	1	3/4	1/2	0.330	10	<b>49254</b>	6
6	1	1	1/2	0.455	10	<b>49256</b>	6
8	1	1	1/2	0.576	5	<b>49258</b>	6



**Viega PEX Press manifold**

**Smart Connect feature**

- Only use with lock clip Part No 58075

- Polymer

- Press connection

- Closed

Note

Does not include mounting hardware

**Model V5636.1**

Outlet(s)	P1	P2	P3	Wt [lb]	Quantity	Part No	DG
4	closed	3/4	1/2	0.300	10	<b>49004</b>	6
6	closed	1	1/2	0.428	10	<b>49206</b>	6

**Stub-Outs**



**Viega PEX Press 90° tub elbow**

- Brazed copper

- Press connection, street

**Model 2820.0ZL**

P	FTG	L1 [in]	L2 [in]	Wt [lb]	Quantity	Part No	DG
1/2	1/2	3	6	0.245	25	<b>92221</b>	6



**Viega PEX Press 90° stub-out**

- Brazed copper

- Press connection, street

**Model 2820.1ZL**

P	FTG	L1 [in]	L2 [in]	Wt [lb]	Quantity	Part No	DG
3/8	1/2	3 1/2	8	0.306	25	<b>92406</b>	6
1/2	1/2	3 1/2	8	0.313	25	<b>92421</b>	6
3/4	3/4	3 1/2	8	0.556	25	<b>92441</b>	6

## PEX Crimp

Offering the reliability and quality needed for potable water systems, Viega PEX Crimp fittings are part of our complete plumbing solution. Matched with our revolutionary Viega ManaBloc water distribution system and the highest rated PEX tubing in the industry, Viega PEX Crimp fittings are a time-tested method of joining PEX.

### FEATURES AND BENEFITS

- EcoBrass® fittings provide better corrosion resistance than other brass fittings
- High-performance PolyAlloy fittings are made in the USA
- Peace of mind from durable materials and quality manufacturing
- In sizes 3/8" to 1"
- Comprehensive 10-year transferable warranty

### CODES AND STANDARDS

- ASTM E84: Specification for Surface Burning Characteristics
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for PEX Insert Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- AWWA C904: Cross-linked Polyethylene (PEX) Pressure Pipe for water service
- CAN/ULC S101: Standard Method of Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Method of Test for Surface Burning Characteristics
- CSA International: Canadian Standard Association
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- ICC: International Plumbing Code
- IAPMO: Uniform Plumbing Code
- NSF/ANSI 61: Drinking Water System Components - Health Effects
- NSF/ANSI 61G: Lead Content Evaluation Procedure to meet < 0.25% average lead content
- NSF/ANSI 14: Plastics Piping System Components and Related Materials
- NSPC: National Standard Plumbing Code
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service

### ZERO LEAD

References to Zero Lead throughout this publication mean product meeting the requirements of NSF 61-G through testing under NSF/ANSI Standard 372 (0.25% or less percent maximum weighted average lead content).