

# Threaded brass manifold straight adapters and bushings

## Project Information

|                                |                 |
|--------------------------------|-----------------|
| Job name:                      | Location:       |
| Engineer:                      | Date submitted: |
| Contractor:                    | Submitted by:   |
| Manufacturer's representative: | Approved by:    |

## Technical data

|                         |  |
|-------------------------|--|
| End type 1              | ISO 228-G 1-1/4"   |
| Temp/pressure ratings   | 73 °F (23 °C) at 160 psi (11 bar)<br>180 °F (82 °C) at 100 psi (6.9 bar)<br>200 °F (93 °C) at 80 psi (5.5 bar) |
| Prop 65 label required? | Yes  |

## Product information and application use

Uponor's Threaded Brass Manifold Bushings are used in TruFLOW™ manifolds. In radiant heating applications, the bushing transitions the R32 manifold union nut to 1" national pipe thread (NPT) and 3/4" threaded connections (PEX or Multi-layer Composite (MLC) tubing with QS-style fittings).



| Part name   | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | H [inch] | Weight per UOM [lbs/UOM] | Material group |
|---|----------|----------|----------|----------|----------|----------|----------|----------|----------|--------------------------|----------------|
| Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT     | A2123210 | 1.918    | 1.687    | 0.985    | 1        | -        | -        | -        | -        | 0.3                      | -              |
| Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT   | A2133275 | 2.018    | 1.75     | 0.985    | -        | -        | -        | -        | -        | 0.44                     | -              |
| Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male | A4143220 | 0.635    | 0.35     | 0.599    | 2.02     | 1.584    | 1.75     | 1.01     | 0.875    | 0.55                     | -              |
| Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male | A4143225 | 0.613    | 0.35     | 0.635    | 2.02     | 1.598    | 1.75     | 1.01     | 0.875    | 0.5                      | -              |

| Part name   | Part no. | End Type 2     |
|---|----------|----------------|
| Threaded Brass Manifold Bushing, R32 Male x 1" Female NPT     | A2123210 | FNPT 1"        |
| Threaded Brass Manifold Bushing, R32 Male x 3/4" Female NPT   | A2133275 | FNPT 3/4"      |
| Threaded Brass Manifold Straight Adapter, R32 Male x R20 Male | A4143220 | ISO 228-G 3/4" |
| Threaded Brass Manifold Straight Adapter, R32 Male x R25 Male | A4143225 | ISO 228-G 1"   |

## Installation

Thread directly into Uponor TruFLOW manifolds. For additional information, refer to the TruFLOW Manifold Instruction Sheet or the Uponor Radiant Floor Heating Installation Handbook.

## Related applications

- Radiant Heating and Cooling Systems
- Permafrost Protection Systems
- Turf Conditioning Systems

## Codes

IMC|IRC|NBC of Canada|UMC

## Standards

CSA B137.5|R32:

## Listings

cNSFus-rfh

## Footnotes

-

## Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517