



### Viega PEX Press 90° stub-out

- Brazed copper
- Press connection, street components

Wall plate Model 2820.4ZL

Р	FTG	L1 [in]	L2 [in]	Wt [lb]	Quantity	Part No	DG
3/8	1/2	31/2	8	0.327	25	92305	6
1/2	1/2	31/2	8	0.371	25	92321	6



#### Viega PEX Press stub-out

- Brazed copper
- Press connection, street components Wall plate

Model 2820.2ZL

½ ½ 8 0.240 25 92609 6   ½ ½ ½ 15 0.422 25 92616 6	Р	FTG	L [in]	Wt [lb]	Quantity	Part No	DG
½ ½ 15 0.422 25 <b>92616</b> 6	1/2	1/2	8	0.240	25	92609	6
	1/2	1/2	15	0.422	25	92616	6

### Lav adapters



# Viega PEX Press lav adapter

**Smart Connect feature** 

- Polymer

- Press connection, lav connection

Model V5613.3

Р	Lav	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.045	1	49324	6
1/2	1/2	0.055	1	49333	6
3/4	3/4	0.080	1	49344	6



### Viega PEX Press adapter Zero Lead

- Equipped with ferrule Part No 53005

- Bronze
- Press connection, compression

components

Brass ferrule

Model 2895ZL

Р	CTS	Wt [lb]	Quantity	Part No	DG
3/8	1/4	0.111	1	97112	6
1/2	1/4	0.115	1	97113	6

# **Closet adapters**



### Viega PEX Press closet adapter **Smart Connect feature**

- Polymer
- Press connection, closet connection

Model V5613.4

Р	Closet	Wt [lb]	Quantity	Part No	DG
3/8	1/2	0.060	1	49223	6
1/2	1/2	0.072	1	49233	6

### **Outlet boxes**



### Viega PEX Press outlet box Zero Lead

- For washing machine
- Color coded handles

components

(2) 1/4 turn brass valves, water hammer arrestors

Model 2872.6ZL

Р	Wt [lb]	Quantity	Part No	DG
1/2	1.944	1	97212	6



### Viega PEX Press outlet box Zero Lead

- For ice maker components

1/4 turn brass valve, water hammer arrestor

Model 2872.7ZL

Р	Wt [lb]	Quantity	Part No	DG
1/2	1.050	1	07220	6



## **PEX Crimp**

Offering the reliability and quality needed for potable water systems, Viega PEX Crimp fittings are part of our complete plumbing solution. Matched with our revolutionary Viega ManaBloc water distribution system and the highest rated PEX tubing in the industry, Viega PEX Crimp fittings are a time-tested method of joining PEX.

#### **FEATURES AND BENEFITS**

- EcoBrass® fittings provide better corrosion resistance than other brass fittings
- · High-performance PolyAlloy fittings are made in the USA
- · Peace of mind from durable materials and quality manufacturing
- In sizes %" to 1"
- Comprehensive 10-year transferable warranty

#### **CODES AND STANDARDS**

- ASTM E84: Specification for Surface Burning Characteristics
- ASTM F876: Standard Specification for PEX Tubing
- ASTM F877: Standard Specification for PEX Water Distribution System
- ASTM F1807/F2159: Standard Specification for PEX Insert Fittings
- ASTM F2023: Standard Test Method for Evaluating the Oxidative Resistance of Cross-linked Polyethylene PEX Tubing and Systems to Hot Chlorinated Water
- AWWA C904: Cross-linked Polyethylene (PEX) Pressure Pipe for water service
- CAN/ULC S101: Standard Method of Test for Surface Burning Characteristics
- CAN/ULC S102.2: Standard Method of Test for Surface Burning Characteristics
- CSA International: Canadian Standard Association
- CSA B137.5: Standard Specification for PEX tubing systems in pressure applications
- ICC: International Plumbing Code
- IAPMO: Uniform Plumbing Code
- NSF/ANSI 61: Drinking Water System Components Health Effects
- NSF/ANSI 61G: Lead Content Evaluation Procedure to meet < 0.25% average lead content
- NSF/ANSI 14: Plastics Piping System Components and Related Materials
- NSPC: National Standard Plumbing Code
- UL 1821: Thermoplastic Sprinkler Pipe and Fittings for Fire Protection Service

### ZERO LEAD

References to Zero Lead throughout this publication mean product meeting the requirements of NSF 61-G through testing under NSF/ANSI Standard 372 (0.25% or less percent maximum weighted average lead content).