

The Best Products, The Best Service...


SERVICE METAL

ONE CALL GETS IT ALL




Concentric & Eccentric Reducers

EXTRA STRONG
Inches / Pounds



Concentric



Eccentric

Nominal Pipe Size	Length (H)	Approximate Weight (in Pounds)
3/4 x 1/2	1.5	.25
1 x 1/2	2	.42
1 x 3/4	2	.43
1 1/4 x 1/2	2	.53
1 1/4 x 3/4	2	.53
1 1/4 x 1	2	.57
1 1/2 x 1/2	2.5	.65
1 1/2 x 3/4	2.5	.65
1 1/2 x 1	2.5	.72
1 1/2 x 1 1/4	2.5	.78
2 x 3/4	3	.94
2 x 1	3	1.0
2 x 1 1/4	3	1.1
2 x 1 1/2	3	1.2
2 1/2 x 1	3.5	1.5
2 1/2 x 1 1/4	3.5	1.7
2 1/2 x 1 1/2	3.5	1.9
2 1/2 x 2	3.5	2.1
3 x 1	3.5	2.2
3 x 1 1/4	3.5	2.3
3 x 1 1/2	3.5	2.4
3 x 2	3.5	2.6
3 x 2 1/2	3.5	2.8
3 1/2 x 1 1/4	4	3.3
3 1/2 x 1 1/2	4	3.3
3 1/2 x 2	4	3.3
3 1/2 x 2 1/2	4	3.5
3 1/2 x 3	4	3.7



The Best Products, The Best Service...

SERVICE METAL

ONE CALL GETS IT ALL

Concentric & Eccentric Reducers – Extra Strong (Continued)

Nominal Pipe Size	Length (H)	Approximate Weight (in Pounds)
4 X 1	4	4
4 X 1 ¼	4	4.1
4 X 1 ½	4	4.2
4 X 2	4	4.3
4 X 2 ½	4	4.6
4 X 3	4	4.7
4 X 3 ½	4	4.9
5 X 2	5	6
5 X 2 ½	5	6.1
5 X 3	5	6.3
5 X 3 ½	5	6.9
5 X 4	5	7.5
6 X 2	5.5	8.6
6 X 2 ½	5.5	9.1
6 X 3	5.5	9.7
6 X 3 ½	5.5	10
6 X 4	5.5	10.7
6 X 5	5.5	11.5
8 X 3	6	15
8 X 3 ½	6	15.9
8 X 4	6	17
8 X 5	6	17.6
8 X 6	6	18.8
10 X 4	7	24.2
10 X 5	7	26.9
10 X 6	7	28.3
10 X 8	8	29.4
12 X 4	8	34.7
12 X 5	8	36.3
12 X 6	8	37.4
12 X 8	8	38.6
12 X 10	8	41.5
14 X 6	13	72.3
14 X 8	13	74.6
14 X 10	13	76.7
14 X 12	13	81



The Best Products, The Best Service...

SERVICE METAL

ONE CALL GETS IT ALL

Concentric & Eccentric Reducers – Extra Strong (Continued)

Nominal Pipe Size	Length (H)	Approximate Weight (in Pounds)
16 X 6	14	89.8
16 X 8	14	91.1
16 X 10	14	93.3
16 X 12	14	95.8
16 X 14	14	98
18 X 10	15	113
18 X 12	15	115
18 X 14	15	117
18 X 16	15	118
20 X 10	20	152
20 X 12	20	155
20 X 14	20	157
20 X 16	20	159
20 X 18	20	162
24 X 16	20	194
24 X 18	20	197
24 X 20	20	201
30 X 18	24	315
30 X 20	24	315
30 X 24	24	315
36 X 20	24	379
36 X 24	24	379
36 X 30	24	379
42 X 24	24	443
42 X 30	24	443
42 X 36	24	443
48 X 30	28	525
48 X 36	28	525
48 X 42	28	525

* Dimensions conform to ASME B16.9 & material conforms to ASTM SA-234 Grade B.