

Tubing



ViegaPEX Ultra tubing

- PEX
- Coil

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5001

| d | L [ft] | Version | Wt [lb] | Quantity | Part No | DG |
|-----|--------|---------|---------|----------|--------------------|----|
| 3/8 | 100 | red | 5.000 | 1 | 32101 ¹ | 1 |
| 3/8 | 500 | red | 21.000 | 1 | 32105 ¹ | 1 |
| 3/8 | 1000 | red | 42.000 | 1 | 32100 | 1 |
| 1/2 | 100 | red | 5.800 | 1 | 32121 ¹ | 1 |
| 1/2 | 300 | red | 17.100 | 1 | 32123 ¹ | 1 |
| 1/2 | 500 | red | 28.000 | 1 | 32125 ¹ | 1 |
| 1/2 | 1000 | red | 58.000 | 1 | 32120 | 1 |
| 3/4 | 100 | red | 11.000 | 1 | 32141 ¹ | 1 |
| 3/4 | 300 | red | 32.100 | 1 | 32143 ¹ | 1 |
| 3/4 | 500 | red | 53.000 | 1 | 32145 ¹ | 1 |
| 1 | 100 | red | 16.900 | 1 | 33323 ¹ | 1 |
| 1 | 300 | red | 50.700 | 1 | 32163 | 1 |
| 1 | 500 | red | 88.000 | 1 | 32165 | 1 |

¹⁾ center pull coil



ViegaPEX Ultra tubing

- PEX
- Straight length

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5001.5

| d | L [ft] | Version | Wt [lb] | Quantity | Part No | DG |
|-----|--------|---------|---------|----------|---------|----|
| 1/2 | 10 | red | 0.540 | 50 | 33272 | 1 |
| 1/2 | 20 | red | 1.060 | 50 | 33120 | 1 |
| 3/4 | 10 | red | 1.020 | 25 | 33275 | 1 |
| 3/4 | 20 | red | 2.040 | 25 | 33145 | 1 |
| 1 | 20 | red | 3.420 | 5 | 33270 | 1 |



ViegaPEX Ultra tubing

- PEX
- Coil

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5002

| d | L [ft] | Version | Wt [lb] | Quantity | Part No | DG |
|-----|--------|---------|---------|----------|--------------------|----|
| 3/8 | 100 | blue | 5.000 | 1 | 32201 ¹ | 1 |
| 3/8 | 500 | blue | 21.000 | 1 | 32205 ¹ | 1 |
| 3/8 | 1000 | blue | 42.000 | 1 | 32200 | 1 |
| 1/2 | 100 | blue | 5.300 | 1 | 32221 ¹ | 1 |
| 1/2 | 300 | blue | 17.100 | 1 | 32223 ¹ | 1 |
| 1/2 | 500 | blue | 26.500 | 1 | 32225 ¹ | 1 |
| 1/2 | 1000 | blue | 55.000 | 1 | 32220 | 1 |
| 3/4 | 100 | blue | 11.000 | 1 | 32241 ¹ | 1 |
| 3/4 | 300 | blue | 32.100 | 1 | 32243 ¹ | 1 |
| 3/4 | 500 | blue | 53.000 | 1 | 32245 ¹ | 1 |
| 1 | 100 | blue | 17.000 | 1 | 32266 | 1 |
| 1 | 300 | blue | 50.700 | 1 | 32263 | 1 |
| 1 | 500 | blue | 88.000 | 1 | 32265 | 1 |

¹⁾ center pull coil



ViegaPEX Ultra tubing

- PEX
- Straight length


Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5002.5

| d | L [ft] | Version | Wt [lb] | Quantity | Part No | DG |
|-----|--------|---------|---------|----------|---------|----|
| 1/2 | 10 | blue | 0.540 | 50 | 33274 | 1 |
| 1/2 | 20 | blue | 1.060 | 50 | 33240 | 1 |
| 3/4 | 10 | blue | 1.020 | 25 | 33277 | 1 |
| 3/4 | 20 | blue | 2.040 | 25 | 33265 | 1 |
| 1 | 20 | blue | 3.420 | 5 | 33271 | 1 |



ViegaPEX Ultra tubing

- For installation between studs
- PEX
- ManaPac

components

Recycled plastic reels

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5004

| d | L [ft] | Reel(s) | Version | Wt [lb] | Quantity | Part No | DG |
|-----|--------|---------|----------|---------|----------|--------------------|----|
| 3/8 | 500 | 2 | red/blue | 58.000 | 1 | 32300 ¹ | 1 |
| 3/8 | 500 | 1 | blue | 28.000 | 1 | 32905 | 1 |
| 3/8 | 500 | 1 | red | 28.000 | 1 | 32805 | 1 |
| 1/2 | 300 | 2 | red/blue | 48.000 | 1 | 32326 ¹ | 1 |
| 1/2 | 300 | 1 | blue | 23.100 | 1 | 32923 | 1 |
| 1/2 | 300 | 1 | red | 23.100 | 1 | 32823 | 1 |

¹⁾ Available while supplies last

Tubing



ViegaPEX Ultra tubing

- PEX
- Coil
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5001**

| d | L [ft] | Version | Wt [lb] | Quantity | Part No | DG |
|-----|--------|---------|---------|----------|--------------------|----|
| 3/8 | 100 | red | 5.000 | 1 | 32101 ¹ | 1 |
| 3/8 | 500 | red | 21.000 | 1 | 32105 ¹ | 1 |
| 3/8 | 1000 | red | 42.000 | 1 | 32100 | 1 |
| 1/2 | 100 | red | 5.800 | 1 | 32121 ¹ | 1 |
| 1/2 | 300 | red | 17.100 | 1 | 32123 ¹ | 1 |
| 1/2 | 500 | red | 28.000 | 1 | 32125 ¹ | 1 |
| 1/2 | 1000 | red | 58.000 | 1 | 32120 | 1 |
| 3/4 | 100 | red | 11.000 | 1 | 32141 ¹ | 1 |
| 3/4 | 300 | red | 32.100 | 1 | 32143 ¹ | 1 |
| 3/4 | 500 | red | 53.000 | 1 | 32145 ¹ | 1 |
| 1 | 100 | red | 16.900 | 1 | 33323 ¹ | 1 |
| 1 | 300 | red | 50.700 | 1 | 32163 | 1 |
| 1 | 500 | red | 88.000 | 1 | 32165 | 1 |

¹⁾ center pull coil



ViegaPEX Ultra tubing

- PEX
- Straight length
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5001.5**

| d | L [ft] | Version | Wt [lb] | Quantity | Part No | DG |
|-----|--------|---------|---------|----------|---------|----|
| 1/2 | 10 | red | 0.540 | 50 | 33272 | 1 |
| 1/2 | 20 | red | 1.060 | 50 | 33120 | 1 |
| 3/4 | 10 | red | 1.020 | 25 | 33275 | 1 |
| 3/4 | 20 | red | 2.040 | 25 | 33145 | 1 |
| 1 | 20 | red | 3.420 | 5 | 33270 | 1 |



ViegaPEX Ultra tubing

- PEX
- Coil
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5002**

| d | L [ft] | Version | Wt [lb] | Quantity | Part No | DG |
|-----|--------|---------|---------|----------|--------------------|----|
| 3/8 | 100 | blue | 5.000 | 1 | 32201 ¹ | 1 |
| 3/8 | 500 | blue | 21.000 | 1 | 32205 ¹ | 1 |
| 3/8 | 1000 | blue | 42.000 | 1 | 32200 | 1 |
| 1/2 | 100 | blue | 5.300 | 1 | 32221 ¹ | 1 |
| 1/2 | 300 | blue | 17.100 | 1 | 32223 ¹ | 1 |
| 1/2 | 500 | blue | 26.500 | 1 | 32225 ¹ | 1 |
| 1/2 | 1000 | blue | 55.000 | 1 | 32220 | 1 |
| 3/4 | 100 | blue | 11.000 | 1 | 32241 ¹ | 1 |
| 3/4 | 300 | blue | 32.100 | 1 | 32243 ¹ | 1 |
| 3/4 | 500 | blue | 53.000 | 1 | 32245 ¹ | 1 |
| 1 | 100 | blue | 17.000 | 1 | 32266 | 1 |
| 1 | 300 | blue | 50.700 | 1 | 32263 | 1 |
| 1 | 500 | blue | 88.000 | 1 | 32265 | 1 |


¹⁾ center pull coil



ViegaPEX Ultra tubing

- PEX
- Straight length
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5002.5**

| d | L [ft] | Version | Wt [lb] | Quantity | Part No | DG |
|-----|--------|---------|---------|----------|---------|----|
| 1/2 | 10 | blue | 0.540 | 50 | 33274 | 1 |
| 1/2 | 20 | blue | 1.060 | 50 | 33240 | 1 |
| 3/4 | 10 | blue | 1.020 | 25 | 33277 | 1 |
| 3/4 | 20 | blue | 2.040 | 25 | 33265 | 1 |
| 1 | 20 | blue | 3.420 | 5 | 33271 | 1 |



ViegaPEX Ultra tubing

- For installation between studs
- PEX
- ManaPac
- components
- Recycled plastic reels
- Technical Data
- PEX designation code 5306
- UV resistance 6 months
- ASTM F876, ASTM F877
- Model V5004**

| d | L [ft] | Reel(s) | Version | Wt [lb] | Quantity | Part No | DG |
|-----|--------|---------|----------|---------|----------|--------------------|----|
| 3/8 | 500 | 2 | red/blue | 58.000 | 1 | 32300 ¹ | 1 |
| 3/8 | 500 | 1 | blue | 28.000 | 1 | 32905 | 1 |
| 3/8 | 500 | 1 | red | 28.000 | 1 | 32805 | 1 |
| 1/2 | 300 | 2 | red/blue | 48.000 | 1 | 32326 ¹ | 1 |
| 1/2 | 300 | 1 | blue | 23.100 | 1 | 32923 | 1 |
| 1/2 | 300 | 1 | red | 23.100 | 1 | 32823 | 1 |

¹⁾ Available while supplies last