

TECHNICAL DATA SHEET

GAS~FLO NATURAL GAS GRILL / B.B.Q. HOSE ASSEMBLIES

Applications: Used To Conduct Natural Gas And Propane In A Gaseous State.

3/8" TYPE I HOSE WITH **GAS~FLO** 3/8" QUICK DISCONNECT

RUBBER - Hose Approved to C.G.A. Standard 8.1 Capacity Natural Gas. Q.D. Rated to 1/2 PSIG
 THERMOPLASTIC - Hose Approved to C.G.A. Standard 8.3 Capacity Natural Gas. Q.D. Rated to 1/2 PSIG



Assemblies come complete with dust plug and cap. Remove "PC" if not required.

PART No.
 I6C Series
 I6TC Series




Description
 Rubber
 Thermoplastic

Above assemblies come with 3/8" **GAS~FLO** Coupler and Nipple

TO BE INSTALLED BY LICENSED GAS FITTERS ONLY.

3/8" GREY HOSE WITH **GAS~FLO** 3/8" QUICK DISCONNECT

CSA Certified to Standard ANSI Z21.54 C.G.A. 8.4 (Thermoplastic) Used To Conduct Natural Gas / Propane In A Gaseous State Up To 1/2 P.S.I. 80,000 BTU/Hr. Capacity Natural Gas



Assemblies come complete with dust plug and cap. Remove "PC" if not required.

PART No.
 I6NGTC Series



Description
 Rubber

CSA Certified to Standard ANSI Z21.54 C.G.A. 8.4 (Metal) Used To Conduct Natural Gas / Propane In A Gaseous State Up To 1/2 P.S.I. 80,000 BTU/Hr. Capacity Natural Gas

PART No.
 I6NGC Series

Description
 Metal

Above assemblies come with 3/8" **GAS~FLO** Coupler and Nipple

TO BE INSTALLED BY LICENSED GAS FITTERS ONLY.