

A KOHLER COMPANY

ACCORD®

Features

- · Allows for future attachment of grab bars
- Modular 4-piece design
- Pivot "snap together" installation
- Wall surround available with smooth finish or glazed tile appearance
- 10-year consumer/3-year commercial limited warranty
- Not recommended for bath only installation
- Caulkless seam installation
- 15" (38.1 cm) bath depth (floor to top of threshold)
- 60-1/4" (153 cm) x 31-1/4" (79.4 cm) x 73-1/4" (186.1 cm) complete unit rough-in dimensions include flanges
- 60" (152.4 cm) x 30" (76.2 cm) x 72" (182.9 cm) complete unit finished dimensions


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ANSI Z124.1.2
- ASTM E162
- ASTM E662
- CSA B45

60" (152.4 cm) BATH AND WALL SURROUND WITH BACKER BOARDS 71140116

ALSO 71140126, 71240116, 71240126



Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Complete Unit Description	Colors/Finishes	
71140116	60" (152.4 cm) bath and wall surround, tile wall, backer boards, left drain	□ 0	☐ Other
71140118	60" (152.4 cm) AFD bath and wall surround, tile wall, backer boards, left drain	□ 0	☐ Other
71140126	60" (152.4 cm) bath and wall surround, tile wall, backer boards, right drain	0	□ Other
71140128	60" (152.4 cm) AFD bath and wall surround, tile wall, backer boards, right drain	□ 0	☐ Other
71240116	60" (152.4 cm) bath and wall surround, smooth wall, backer boards, left drain	0	□ Other
71240118	60" (152.4 cm) AFD bath and wall surround, smooth wall, backer boards, left drain	□ 0	☐ Other
71240126	60" (152.4 cm) bath and wall surround, smooth wall, backer boards, right drain	0	□ Other
71240128	60" (152.4 cm) AFD bath and wall surround, smooth wall, backer boards, right drain	0	□ Other

ACCORD®

Technical Information

Fixture*:				
Basin area:				
Bathing well	46-1/4" (117.5 cm) x 20-1/2" (52.1 cm)			
Top area	52-1/4" (132.7 cm) x 22-1/2" (57.2 cm)			
To overflow:				
Water depth	11" (27.9 cm)			
Capacity	34 gal (128.7 L)			
* Approximate measurements for comparison only.				

Model	door maximum width	door maximum height		
71140116	56-3/4" (144.1 cm)	56-1/2" (143.5 cm)		
71140118	,	,		
71140126				
71140128				
71240116				
71240118				
71240126				
71240128				

Installation Notes

Install this product according to the installation guide.

Product is designed to be used with a single-handle mixer valve with an escutcheon cover not to exceed 7-3/4" (19.7 cm) in width.

Size the drain cutout to fit the drain assembly that will be used.

Studs should be positioned roughly as shown.

Bath cannot be installed without the wall surround.

The width of the module gets 5/8" (1.6 cm) narrower at the back. Furring strips (approximately 1/4" (6 mm)) should be used at the back corner studs if the drywall will overlap the nailing flange.

