

Submittal Data Information

101-005

Boiler Feed Valves, Dual Controls, Backflow Preventers & Combination Boiler Feed & Backflow Preventer Valves

Effective: April 5, 2019 Supersedes: January 26, 2018

Job: Engi	ineer:	Contractor:	Rep:	-
ITEM NO.	MODEL NO.			

Features

- Fast Fill Rate on All Models
- Exclusive Fast Fill Lever Lock
- Built-In Check to Prevent Emptying the System if Incoming Pressure Fails
- Adjustable Set Pressure of 10 to 25 psi
- Pressure Setting Adjustment Separated from Fast Fill Lever for Easy, Fast Adjustment

 Both the Backflow Preventer and the Combination Boiler Feed & Backflow Preventer Valve Carry These Certifications:




Listing 1012 - 2009




Purpose

To automatically feed water to a system whenever pressure in the system drops below the pressure setting of the valve. The dual control combines the boiler feed valve with an in-line pressure relief valve connected at the outlet end. The backflow prevents contamination of the potable water if supply pressure should fail.

Boiler Feed Valve








Model 335

* Dimensions for reference purposes only.

Models 323									1			1		1		iensions i	OI ICICICI	Г	oses offiy.
Models	Max Tei	Fluid mp	Max S	erforma Supply ess.		ssure nge	Fac Set	tory ting	Body	Inlet	Outlet	,	A	1	В	С		Ship Wt.	
	F°	C°	psi	kPa	psi	kPa	psi	kPa				in.	mm	in.	mm	in.	mm	lbs.	Kg
329									Cast Iron	1/2" Union SWT	1/2" NPT	4-1/4	108	3-3/4	95	1-3/8	35	1.75	1.1
329-T									Cast Iron	1/2" Union NPT	1/2" NPT	4-3/4	111	3-3/4	95	1-3/8	35	1.75	1.1
329-H									Cast Iron	1/2" Union Press	1/2" NPT	5-1/2	140	3-3/4	95	1-3/8	35	1.75	1.1
335									Brass	3/4" NPT	3/4" NPT	3-3/4	95	3-3/4	95	1-3/8	35	2.4	1.1
335U-050-C	212°	100°	100	689	10-25	69-172	12	83	Brass	1/2" Union SWT	1/2" NPT	4-1/4	108	3-3/4	95	1-3/8	35	2.5	1.2
335U-050-T									Brass	1/2" Union NPT	1/2" NPT	4-1/4	108	3-3/4	95	1-3/8	35	2.5	1.2
335U-050-H									Brass	1/2" Union Press	1/2" NPT	5-1/4	133	3-3/4	95	1-3/8	35	2.5	1.2
335U-075-C									Brass	3/4" Union SWT	3/4" NPT	4-1/2	114	3-3/4	95	1-3/8	35	2.5	1.2
335U-075-T										Brass	3/4" Union NPT	3/4" NPT	4-1/4	108	3-3/4	95	1-3/8	35	2.5

Dual Controls




Models 334 & 334-T/H

* Dimensions for reference purposes only.

	Performance Data																
Models	Max Fluid Temp		Max Supply Press.		Relief Valve Setting		Body	Inlet	Outlet	A		В		С		Ship Wt.	
	F°	C°	psi	kPa	psi	kPa				in.	mm	in.	mm	in.	mm	lbs.	Kg
334					30	207	Cast Iron	1/2" Union SWT	1/2" NPT	7-1/4	184	3-3/4	95	1-3/8	35	3.9	1.8
334-T	212°	100°	100	689			Cast Iron	1/2" Union NPT	1/2" NPT	7-3/8	187	3-3/4	95	1-3/8	35	3.9	1.8
334-H							Cast Iron	1/2" Union Press	1/2" NPT	8-3/8	213	3-3/4	95	1-3/8	35	3.9	1.8

Backflow Preventer





Listing 1012 - 2009




Listing B64.3 - 11

^{*} Dimensions for reference purposes only.

	Performance Data						-										
Models	Max T	Гетр	Max Wor	king Press.	Design Pressure Range		Body	Inlet	Outlet	A		В		С		Ship Wt.	
	F°	C°	psi	kPa	psi	kPa				in.	mm	in.	mm	in.	mm	lbs.	Kg
3192-C			175	1206	25.250	172-1724	Brass	1/2" Union SWT	1/2" Union SWT	4-1/4	108	7/8	25	1-5/8	41	1.5	0.7
3192-T	250°	121°					Brass	1/2" Union NPT	1/2" Union NPT	4-1/8	105	7/8	25	1-5/8	41	1.5	0.7
3193-C	250	121	175	1206	25-250		Brass	3/4" Union SWT	3/4" Union SWT	4-7/8	124	7/8	25	1-5/8	41	1.5	0.7
3193-T							Brass	3/4" Union NPT	3/4" Union NPT	4-1/8	105	7/8	25	1-5/8	41	1.5	0.7

Combination Boiler Feed & Backflow Preventer Valve





Listing 1012 - 2009



Listing B64.3 - 11

* Dimensions for reference purposes only.

			Perfo	rmance Da	ita												
Models	Max Fluid Temp		Max Supply Press.		Max Working Press.		Body	Inlet	Outlet	A		В		С		Ship Wt.	
	F°	C°	psi	kPa	psi kPa					in.	mm	in.	mm	in.	mm	lbs.	Kg
3492-050-C						172	Cast Iron/Brass	1/2" Union SWT	1/2" NPT	8-1/8	206	3-3/4	95	1-5/8	41	4	1.8
3492-050-T							Cast Iron/Brass	1/2" Union NPT	1/2" NPT	8-1/4	211	3-3/4	95	1-5/8	41	4	1.8
3492-050-H					25		Cast Iron/Brass	1/2" Union Press	1/2" NPT	9-3/8	238	3-3/4	95	1-5/8	41	4	1.8
3492-050-BC	212°	100°	100				Brass	1/2" Union SWT	1/2" NPT	7-7/8	199	3-3/4	95	1-5/8	41	4	1.8
3492-050-BT	212	100°	100	689	25	172	Brass	1/2" Union NPT	1/2" NPT	8	203	3-3/4	95	1-5/8	41	4	1.8
3492-050-BH							Brass	1/2" Union Press	1/2" NPT	9-1/8	232	3-3/4	95	1-5/8	41	4	1.8
3493-075-BC							Brass	3/4" Union SWT	3/4" NPT	7-1/2	191	3-3/4	95	1-5/8	41	4	1.8
3493-075-BT							Brass	3/4" Union NPT	3/4" NPT	7-1/4	183	3-3/4	95	1-5/8	41	4	1.8



Taco, Inc., 1160 Cranston Street, Cranston, RI 02920 | Tel: (401) 942-8000 | FAX: (401) 942-2360 **Taco (Canada), Ltd.,** 8450 Lawson Road, Suite #3, Milton, Ontario L9T 0J8 | Tel: (905) 564-9422 | FAX: (905) 564-9436 Visit our web site: www.TacoComfort.com | ©2019 Taco, Inc.



Models 3192 & 3193