

**5 Choose the Blade Profile**

**A) DEMOLITION BLADES:**

**MAXIMUM DURABILITY**

- A thicker, more rigid blade body resists fracturing and bending

**STRAIGHTER CUTS**

- The 1" tall blade body reduces blade twisting for straighter, more accurate cuts



**B) STANDARD BLADES:**

- Traditional blade thickness and profile



**C) SCROLL CUTTING BLADES:**

- Low profile for tight contour cutting



**WOOD CUTTING SAWZALL® BLADES**

Optimized for best cutting performance in nail-embedded dimensional lumber, OSB, plywood and other engineered lumbers.



**FAST CUTTING**

- Precision forming process creates sharper teeth



**EASY PLUNGING**

- Full raker tooth on blade tip

| Description    | TPI | Length | Height | Width  | 5 Pack     | 25 Pack    | 50 Pack    | Bulk Pack  | Qty | Application |
|----------------|-----|--------|--------|--------|------------|------------|------------|------------|-----|-------------|
|                | 6   | 6"     | 3/4"   | 0.050" | 48-00-5035 | -          | 48-01-6035 | 48-01-7035 | 100 |             |
| <b>THE AX™</b> | 5/8 | 6"     | 1"     | 0.062" | 48-00-5021 | 48-00-8021 | -          | 48-01-7021 | 100 |             |
|                | 6   | 9"     | 3/4"   | 0.050" | 48-00-5036 | 48-00-8036 | 48-01-6036 | 48-01-7036 | 100 |             |
| <b>THE AX™</b> | 5/8 | 9"     | 1"     | 0.062" | 48-00-5026 | 48-00-8026 | -          | 48-01-7026 | 100 |             |
|                | 6   | 12"    | 3/4"   | 0.050" | 48-00-5037 | -          | 48-01-6037 | 48-01-7037 | 100 |             |
| <b>THE AX™</b> | 5/8 | 12"    | 1"     | 0.062" | 48-00-5027 | 48-00-8027 | -          | 48-01-7027 | 100 |             |

See the specialty SAWZALL® blade section for additional wood cutting options, including 4/6 TPI scrolling blades

**GENERAL PURPOSE SAWZALL® BLADES**

Designed for versatile cutting performance across the broadest selection of materials including nail-embedded wood, plastics, ferrous and non-ferrous metals.



**LONG LIFE**

- Double relief angle reduces tooth stress



**FAST CUTTING**

- Precision forming process creates sharper teeth

| Description         | TPI   | Length | Height | Width  | 5 Pack     | 25 Pack    | 50 Pack    | Bulk Pack  | Qty | Application |
|---------------------|-------|--------|--------|--------|------------|------------|------------|------------|-----|-------------|
|                     | 8/12  | 6"     | 3/4"   | 0.050" | 48-00-5091 | -          | 48-01-6091 | 48-01-7091 | 100 |             |
|                     | 8/12  | 6"     | 3/4"   | 0.050" | 48-00-4091 | -          | -          | 48-01-9091 | 50  |             |
| <b>THE WRECKER™</b> | 8     | 6"     | 1"     | 0.062" | 48-00-5701 | 48-00-8701 | -          | 48-01-7701 | 100 |             |
|                     | 8/12  | 8"     | 3/4"   | 0.050" | 48-00-5093 | 48-00-8093 | 48-01-6093 | 48-01-7093 | 100 |             |
|                     | 8/12  | 8"     | 3/4"   | 0.050" | 48-00-4093 | -          | -          | 48-01-9093 | 50  |             |
| <b>THE WRECKER™</b> | 8     | 9"     | 1"     | 0.062" | 48-00-5706 | 48-00-8706 | -          | 48-01-7706 | 100 |             |
|                     | 8/12  | 12"    | 3/4"   | 0.050" | 48-00-5094 | -          | 48-01-6094 | -          | -   |             |
| <b>THE WRECKER™</b> | 8     | 12"    | 1"     | 0.062" | 48-00-5711 | 48-00-8711 | -          | 48-01-7711 | 100 |             |
|                     | 10/14 | 8"     | 5/8"   | 0.035" | 48-00-5193 | -          | -          | -          | -   | 1/4" - 3/8" |
|                     | 10/14 | 12"    | 5/8"   | 0.035" | 48-00-5194 | -          | -          | -          | -   | 1/4" - 3/8" |