

ProPEX® Lead-free (LF) Brass Commercial Ball Valve

Submittal Information

Revision B: Dec. 23, 2014

Project Information

Job Name:

Location:

Part No. Ordered:

Engineer:

Date Submitted:

Contractor:

Submitted By:

Manufacturer's Representative:

Approved By:

Technical Data

Material (body, ball and stem):	C69300 Brass
Maximum Temperature (no pressure):	250°F (121°C)
Minimum Fluid Temperature:	-30°F (-34°C)
Maximum Working Pressure:	250 psi



Product Information and Application Use

Use Uponor ProPEX® Lead-free Brass Commercial Ball Valves for all commercial PEX piping applications.¹ Both ends are manufactured with the ProPEX fitting for direct connections to Uponor PEX piping.

Note: These valves are compatible with applications using a propylene glycol mixture up to a maximum of 50% propylene glycol.

✓ Description	Part Number	Length	Width	Weight	Cv
ProPEX LF Brass Commercial Ball Valve (full port), ½" PEX x ½" PEX	LFC4825050	2.75"	0.92"	0.36 lbs.	7.0
ProPEX LF Brass Commercial Ball Valve (full port), ¾" PEX x ¾" PEX	LFC4827575	3.25"	1.28"	0.52 lbs.	18.7
ProPEX LF Brass Commercial Ball Valve (full port), 1" PEX x 1" PEX	LFC4821010	4.27"	1.81"	1.3 lbs.	29.0
ProPEX LF Brass Commercial Ball Valve (full port), 1¼" PEX x 1¼" PEX	LFC4821313	4.75"	1.81"	1.44 lbs.	54.7
ProPEX LF Brass Commercial Ball Valve (full port), 1½" PEX x 1½" PEX	LFC4821515	5.68"	2.07"	2.12 lbs.	68.2
ProPEX LF Brass Commercial Ball Valve (full port), 2" PEX x 2" PEX	LFC4822020	7.125"	2.84"	4.18 lbs.	132.2
Stem Extension Kit for ½" and ¾" Valves	F5630001	2.625"	0.906"	0.31 lbs.	N/A
Stem Extension Kit for 1" and 1¼" Valves	F5630002	2.625"	1.063"	0.48 lbs.	N/A
Stem Extension Kit for 1½" and 2" Valves	F5630003	2.625"	1.26"	0.57 lbs.	N/A

Installation

Install valve and stem extension kit according to local building code. Do not dismantle. Refer to the Uponor Professional Plumbing Installation Guide or the Uponor Plumbing Design Assistance Manual (PDAM) for additional information.

Standards

CSA B137.5; ASTM F877; ASTM F1960; NSF-359

Codes

IPC; UPC; NSPC; NPC of Canada

Listings

ANSI/NSF 14- and 61-certified; U.P. Code, Annex G, NSF-359

Related Applications

PEX-a Plumbing Systems
 Radiant Heating and Cooling Systems
 Snow and Ice Melting Systems
 Permafrost Protection Systems
 Turf Conditioning Systems

Contact Information

Uponor, Inc.
 5925 148th Street West
 Apple Valley, MN 55124 USA
 Phone: 800.321.4739
 Fax: 952.891.1409
 www.uponorpro.com
 www.uponorengineering.com

Uponor Ltd.
 2000 Argentia Rd., Plaza 1, Ste. 200
 Mississauga, ON L5N 1W1 CANADA
 Phone: 888.994.7726
 Fax: 800.638.9517
 www.uponorpro.com
 www.uponorengineering.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.