



## RESIDENTIAL/COMMERCIAL First Stage Regulators Type 988HP



988HP-04

### Product description

The first stage regulator reduces the inlet pressure, coming from the container, to a medium level inlet pressure for a second stage regulator. Therefore Type 988 HP regulators are designed for Type A or Type C installations found in the Installations section.

They have to be used outdoors in correct mounting position with vent-hole turned downwards. In their standard version the Type 988 HP regulators are delivered with vent-hole turned in line with the outlet fitting.

### Technical Specifications

**Body And Cover:** Aluminium  
**Diaphragm:** Reinforced  
**Supplying Pressure:** 25-250 PSIG  
**Cover Screws:** Stainless Steel  
**Gas Type:** Propane  
**Setting Point:** inlet Pressure 100 PSIG, 140,000 BTU, Outlet Pressure 10 PSIG  
**Provided Flows:** Flow Based On 25 PSIG Inlet Pressure and 20% Drop (In accordance with UL 144)  
 Type 988HP - L 6.027 x W 4.33 x H 4.94" Weight: 48.75 oz

Type (Part No.)	Capacities in BTU/hr propane	Inlet connection, inches	Outlet connection, inches	Outlet adjustment range, PSIG	Outlet pressure setting, PSIG
988HP - 07 (98.1.890.0007)	2,000,000	1/2" NPT	1/2" NPT	4 to 6	5
988HP - 08 (98.1.890.0008)		POL			
988HP - 09 (98.1.890.0009)	2,250,000		3/4" NPT		
988HP - 04 (98.1.890.0004)	2,100,000	1/2" NPT	1/2" NPT		
988HP - 01 (98.1.890.0001)	2,400,000	3/4" NPT		3/4" NPT	
988HP - 05 (98.1.890.0005)	2,100,000	POL	1/2" NPT		
988HP - 06 (98.1.890.0006)	2,250,000		3/4" NPT		

INSTALLATION  
INSTRUCTIONS

RV AND OUTDOOR  
COOKING REGULATORS

AUTOGAS  
EQUIPMENT

FILLING  
HEADS

BULK STORAGE AND  
TRUCK EQUIPMENT

DOT/ASME  
CONTAINER VALVES

REGULATORS