

SJE VERTICALMASTER® Pump Switch

Mechanically-activated switch designed for direct control of pumps up to 1/2 HP at 120 VAC and 1 HP at 230 VAC.

This mechanically-activated pump switch is designed to operate in non-potable water and sewage applications with limited space. It works well in small sump chambers, effluent applications, and laundry trays, as well as in large tanks.



The SJE VerticalMaster® pump switch is not sensitive to turbulence.

It is available for pump down applications only.



FEATURES

- Heavy-duty contacts.
- Controls pumps up to 1/2 HP at 120 VAC and 1 HP at 230 VAC.
- Adjustable pumping range of .75 to 6.5 inches (2 to 17 cm).
- Includes standard boxed packaging.
- UL Recognized for use in non-potable water and sewage.
- CSA Certified.
- Five-year limited warranty.



OPTIONS

This switch is available:

- with a 120 VAC or 230 VAC piggy-back plug.
- without a plug for direct wiring in 120 VAC or 230 VAC applications.
- in standard cable lengths of 10, 15, 20, or 30 feet and 3, 5, 6, or 10 meters (longer lengths available).

SPECIFICATIONS

CABLE: flexible 16 gauge, 2 conductor (UL, CSA) SJOW or SJTOW, water-resistant (CPE)

MOUNTING BRACKET & HOSE CLAMP: stainless steel

LIFT ROD: injection molded acetal plastic

FLOAT STOP: neoprene

SWITCH AND FLOAT HOUSING: high impact, corrosion resistant, PVC housing for use in sewage and non-potable water up to 125°F (52°C)

overall dimensions: 12 inch high x 5 inch x 3 inch wide (30.5 cm high x 12.7 cm x 7.6 cm wide)

switch housing dimensions (excluding cable entrance): 2 inch high x 2.8 inch wide (5 cm high x 7.1 cm wide)

float housing dimensions: 2.3 inch high x 2.7 inch wide (5.8 cm high x 6.9 cm wide)

ELECTRICAL:

120 VAC 50/60Hz Single Phase:

Maximum Pump Running Current:

13 amps

Maximum Pump Starting Current:

60 amps

Recommended Pump HP:

1/2 HP or less

230 VAC 50/60Hz Single Phase:

Maximum Pump Running Current:

12 amps

Maximum Pump Starting Current:

60 amps

Recommended Pump HP:

1 HP or less

NOTE: This switch must be used with pumps that provide integral thermal overload protection.

SJE
Rhombus

PO Box 1708, Detroit Lakes, MN 56502

1-888-DIAL-SJE • 1-218-847-1317

1-218-847-4617 Fax

email: customer.service@sjerhombus.com

www.sjerhombus.com


121

SEE BACKSIDE FOR ORDERING INFORMATION.
SEE PRICE BOOK FOR LIST PRICE.

SJE VERTICALMASTER® Pump Switch

Mechanically-activated pump switch designed for direct control of pumps up to 1/2 HP at 120 VAC and 1 HP at 230 VAC.

ORDERING INFORMATION

PUMP DOWN ONLY 		Shipping Weight
Part Number	Description	
1003590	10VM1WP	1.73 lbs.
1003772	10VM2WP	1.77 lbs.
1003776	10VMWOP	1.65 lbs.
1003769	15VM1WP	2.08 lbs.
1003773	15VM2WP	2.12 lbs.
1003777	15VMWOP	2.00 lbs.
1003770	20VM1WP	2.43 lbs.
1003774	20VM2WP	2.47 lbs.
1003778	20VMWOP	2.35 lbs.
1003771	30VM1WP	3.13 lbs.
1003775	30VM2WP	3.17 lbs.
1003779	30VMWOP	3.05 lbs.

1 = 120VAC 2 = 230VAC WP = With Plug WOP = With Out Plug

NOTE: Descriptions are grouped by cable length measured in feet (10, 15, 20, 30).

SEE PRICE BOOK FOR LIST PRICE.

OPTIONS

MOUNTING BRACKET AND HOSE CLAMP are standard.

PACKAGING
Boxed - standard

ADDITIONAL CABLE
Longer cable lengths available. Please call for details.

UL Recognized for
Water & Sewage



SPECIFICATIONS

PUMPING RANGE: 0.75 to 6.5 inches (2 cm to 17 cm)

CABLE: flexible 16 gauge, 2 conductor (UL, CSA) SJOW or SJTOW, water-resistant (CPE).

MOUNTING BRACKET AND CLAMP: stainless steel

LIFT ROD: injection molded acetal plastic

FLOAT STOP: neoprene

SWITCH AND FLOAT HOUSING: high impact, corrosion resistant, PVC housing for use in sewage and non-potable water up to 125°F (52°C)

- Overall dimensions: 12 inch high x 5 inch x 3 inch wide (30.5 cm x 12.7 cm x 7.6 cm)
- Switch housing dimensions: 2 inch high x 2.8 inch diameter (5 cm x 7.1 cm)
- Float housing dimensions: 2.3 inch high x 2.8 inch diameter (5.8 cm x 6.9 cm)

ELECTRICAL:

Voltage 50Hz/60Hz Single Phase	Max. Pump Run Current	Max. Pump Start Current	Recommended Pump HP
120 VAC	13 amps	60 amps	1/2 HP or less
230 VAC	12 amps	60 amps	1 HP or less

OTHER INFORMATION

PUMP DOWN is normally open contacts for emptying.

DIRECT WIRING

Units used for direct wiring (without plug) may be used in either 120 VAC or 230 VAC applications within specified amp ratings.

www.sjrhombus.com

customer.service@sjrhombus.com

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) / Fax 218-847-4617

Product offering and pricing are subject to change without notice.
Please visit www.sjrhombus.com for the most current information.