

TITAN MAX[®]

DEFINITE PURPOSE CONTACTORS

WHEN DEPENDABILITY IS A MUST...

● **ELECTRICAL ENDURANCE**

Tested up to 250,000 cycles

● **MULTIPLE CONFIGURATIONS**

Available in 1+, 2, 3 and 4 Poles

● **LONG MECHANICAL LIFE**

Tested up to 1,000,000 cycles

● **FULLY ENCLOSED BODY**

Thermosplastic housing keeps it free of dirt and bugs for maximum endurance

● **COMPACT FOOTPRINT**

Makes it ideal for AC applications versus other contactors



ADDITIONAL FEATURES

- DROP IN FURNAS REPLACEMENT
- SUPERIOR COPPER COIL
- UNIVERSAL MOUNTING PLATE
- ACCEPTS AUXILIARY SWITCHES
- REMOVABLE COVER
- MEETS ARI 780/790 STANDARD
- MOUNTING LUGS ON ALL CONFIGURATIONS

TITAN MAX[®] HAS YOU COVERED

A SOLUTION FROM **Packard**

CROSS REFERENCE

Item ID	F/L Inductive Amps	Locked Rotor Amps 240/480/600	Resistive Amps	Coil Voltage	Industry No.	Direct Replacement for Furnas	Accepts Aux. Switch*
Titan Max 1 Pole							
TMX125A2	25	150/125/100	35	24		45DG10AJA	
TMX125B2	25	150/125/100	35	120		45DG10AFA	
TMX125C2	25	150/125/100	35	208/240		45DG10AGA	
TMX130A2	30	180/150/120	40	24	61720	45EG10AJA	45EG10AJAL
TMX130B2	30	180/150/120	40	120	61721	45EG10AFA	45EG10AFAL
TMX130C2	30	180/150/120	40	208/240	61722	45EG10AGA	45EG10AGAL
TMX140A2	40	240/200/160	50	24	61730	45GG10AJA	45GG10AJAL
TMX140B2	40	240/200/160	50	120	61731	45GG10AFA	45GG10AFAL
TMX140C2	40	240/200/160	50	208/240	61732	45GG10AGA	45GG10AGAL
Titan Max 2 Pole							
TMX225A2	25	150/125/100	35	24		42AF15AJ	45DG20AJ
TMX225B2	25	150/125/100	35	120		42AF15AF	45DG20AF
TMX225C2	25	150/125/100	35	208/240		42AF15AG	45DG20AG
TMX230A2	30	180/150/120	40	24	61745	42BF15AJ	45EG20AJL
TMX230B2	30	180/150/120	40	120	61746	42BF15AF	45EG20AFL
TMX230C2	30	180/150/120	40	208/240	61747	42BF15AG	45EG20AGL
TMX240A2	40	240/200/160	50	24	61755	42CF15AJ	45GG20AJL
TMX240B2	40	240/200/160	50	120	61756	42CF15AF	45GG20AFL
TMX240C2	40	240/200/160	50	208/240	61757	42CF15AG	45GG20AGL
Titan Max 3 Pole							
TMX330A2	30	180/150/120	40	24	61430	42BF35AJ	Yes
TMX330B2	30	180/150/120	40	120	61431	42BF35AF	Yes
TMX330C2	30	180/150/120	40	208/240	61432	42BF35AG	Yes
TMX340A2	40	240/200/160	50	24	61445	42CF35AJ	Yes
TMX340B2	40	240/200/160	50	120	61446	42CF35AF	Yes
TMX340C2	40	240/200/160	50	208/240	61447	42CF35AG	Yes
TMX350A2	50	300/250/200	65	24	61460	42DF35AJ	Yes
TMX350B2	50	300/250/200	65	120	61461	42DF35AF	Yes
TMX350C2	50	300/250/200	65	208/240	61462	42DF35AG	Yes
TMX360A2	60	360/300/240	75	24	61470	42EF35AJ	Yes
TMX360B2	60	360/300/240	75	120	61471	42EF35AF	Yes
TMX360C2	60	360/300/240	75	208/240	61472	42EF35AG	Yes
TMX375A2	75	450/375/300	90	24	61480	42FE35AJ106	Yes
TMX375B2	75	450/375/300	90	120	61481	42FE35AF106	Yes
TMX375C2	75	450/375/300	90	208/240	61482	42FE35AG106	Yes
TMX390A2	90	540/450/360	120	24	61490	42GE35AJ106	Yes
TMX390B2	90	540/450/360	120	120	61491	42GE35AF106	Yes
TMX390C2	90	540/450/360	120	208/240	61492	42GE35AG106	Yes
Titan Max 4 Pole							
TMX430A2	30	180/150/120	40	24		42BF25AJ	Yes
TMX430B2	30	180/150/120	40	120		42BF25AF	Yes
TMX430C2	30	180/150/120	40	208-240		42BF25AG	Yes
TMX440A2	40	240/200/160	50	24		42CF25AJ	Yes
TMX440B2	40	240/200/160	50	120		42CF25AF	Yes
TMX440C2	40	240/200/160	50	208-240		42CF25AG	Yes

*Flexible auxiliary switch options allow you to select any of the Titan Max auxiliary switches depending on your application.

TMX1NC (SPST NC), **TMX1NO** (SPST NO), **TMX2NC** (DPST NC), **TMX2NO** (DPST NO), **TMX1NC/NO** (DPST 1NC + 1NO), **TMXSPDT1** (SPDT - left position), **TMXSPDT2** (SPDT - right position), **TMX2SPDT** (2xSPDT) will fit any 3 pole, 30 – 60 Amp Titan Max contactor. **TMX7590NO** (SPST NO), **TMX7590NC** (SPST NC), **TMX7590SPDT** (SPDT) will fit any 3 pole, 75 – 90 Amp Titan Max contactor.