Copper Pigtails 912 and 913 Series

Application

Pigtails are available in a variety of connections, sizes and styles. Care should always be taken in selecting the proper pigtail for a particular application.

Note: RegO recommends a new pigtail be installed with every new and replaced regulator.


- Features
 Heavy duty construction.
- Individually soldered connections to the copper tubing.
- Each pigtail is individually tested prior to shipment.

Materials

Tubing	Copper
Connection	Brass







Bent Pigtails Ordering Information

		Part Number			
	Approximate	%" Tube	Type/Degree of		
Connections	Length	%" Hex Short Nipple	Bend		
1/4" M. NPT x M. POL	5"	913JS05A	90°		
	1	913PS05A			
M. POL x		913PS12G	270° Right Hand		
M. POL		913PS12H	270° Left Hand		
		913PS12S	360°		

Straight Pigtails Ordering Information

		Part Number		
	¾" Tube		%" Tube	
Connections	Approximate Length	%" Hex Short Nipple	1½" Hex Long Nipple	%" Hex Short Nipple
	5"	-	1/2"	913JS05
M.POL x M.POL	12"	912PS12	-	913PS12
	20"	912PS20	912PA20	913PS20
	30"	912PS30	-	913PS30
	36"	912PS36	912PA36	913PS36
	48"	912PS48	912PA48	913PS48
1/4" Inverted Flare x M.POL	12"	912FS12	-	-
	20"	912FS20	912FA20	-
	30"	912FS30	-	-
	36"	912FS36	-	-
¼" M.NPT x M.POL	5"	-	-	913JS05
	12"	912JS12	-	-
	20"	912JS20	-	-
	36"	912JS36	-	-
½" M.NPT x M.Pol	12"	-	-	913LS12
½" M.NPT x ¾" M NPT	12"	-	-	913KL12

Dielectric Pigtails



Part Number	Approximate Length	Tube	Connections
D912P12	12"		
D912P20	20"	1/4"	M.POL x M.POL
D912P30	30"		02
D912J12	12"		
D912J20	20"		1/4" M.NPT x M.POL
D912J30	30"		W 02
D913P12	12"		
D913P20	20"		M.POL x M.POL
D913P30	30"	3/8"	02
D913J12	12"	78"	
D913J20	20"		1/4" M.NPT x M.POL
D913J20	30"		02