


MXZ-3C30NA4 2.5-TON MULTI-ZONE INVERTER HEAT-PUMP SYSTEM



Job Name:

System Reference:

Date:



FEATURES

- Variable speed INVERTER-driven compressor
- Optional base pan heater
- Quiet outdoor unit operation as low as 52 dB(A)
- High-pressure protection
- Compressor thermal protection
- Compressor overcurrent detection
- Fan motor overheating/voltage protection
- Blue Fin anti-corrosion treatment applied to the outdoor unit heat exchanger for increased coil protection and longer life
 - Rated for 2,000 hours spraying time per ASTM B117 Standard

SPECIFICATIONS: MXZ-3C30NA4

Cooling ¹ (Non-Ducted // Mix (Low-static) // Ducted (Low-static) Mix (High-static) // Ducted (High-static))	Maximum Capacity	BTU/H	28,400 // 28,400 // 28,400 28,400 // 28,400	
	Rated Capacity	BTU/H	28,400 // 27,900 // 27,400 27,900 // 27,400	
	Minimum Capacity	BTU/H	11,600 // 11,300 // 11,000 11,900 // 12,200	
	Maximum Power Input	W	4,040 // 4,000 // 3,960 4,045 // 4,050	
	Rated Power Input	W	2,670 // 2,755 // 2,840 2,762 // 2,854	
	Power Factor (208V, 230V)	%	99.0, 99.0 // 99.0, 99.0 // 99.0, 99.0 99.0, 99.0 // 99.0, 99.0	
Heating at 47°F ² (Non-Ducted // Mix (Low-static) // Ducted (Low-static) Mix (High-static) // Ducted (High-static))	Maximum Capacity	BTU/H	36,000 // 36,000 // 36,000 36,000 // 36,000	
	Rated Capacity	BTU/H	28,600 // 28,100 // 27,600 28,100 // 27,600	
	Minimum Capacity	BTU/H	18,100 // 18,300 // 18,500 17,150 // 16,200	
	Maximum Power Input	W	3,700 // 3,900 // 4,100 3,900 // 4,100	
	Rated Power Input	W	2,149 // 2,185 // 2,220 2,198 // 2,247	
	Power Factor (208V, 230V)	%	99.0, 99.0 // 99.0, 99.0 // 99.0, 99.0 99.0, 99.0 // 99.0, 99.0	
Heating at 17°F ³ (Non-Ducted // Mix (Low-static) // Ducted (Low-static) Mix (High-static) // Ducted (High-static))	Maximum Capacity	BTU/H	21,000 // 21,000 // 21,000 21,000 // 21,000	
	Rated Capacity	BTU/H	18,600 // 18,200 // 17,800 18,200 // 17,800	
	Maximum Power Input	W	2,860 // 2,910 // 2,960 2,910 // 2,960	
	Rated Power Input	W	1,820 // 1,860 // 1,900 1,876 // 1,932	
	Maximum Capacity	BTU/H	19,800 // 19,800 // 19,800 19,800 // 19,800	
Heating at 5°F ⁴ (Non-Ducted // Mix (Low-static) // Ducted (Low-static) Mix (High-static) // Ducted (High-static))	Maximum Power Input	W	3,100 // 3,205 // 3,310 3,205 // 3,310	
	SEER2		19.0 // 17.6 // 16.2 17.6 // 16.2	
	EER2 ¹		10.6 // 10.1 // 9.6 10.1 // 9.6	
	HSPF2 (IV)		10.0 // 9.4 // 8.8 9.4 // 8.8	
	COP at 47°F ²		3.9 // 3.75 // 3.6 3.75 // 3.6	
	COP at 17°F at Maximum Capacity ³		2.15 // 2.11 // 2.07 2.12 // 2.08	
Efficiency (Non-Ducted // Mix (Low-static) // Ducted (Low-static) Mix (High-static) // Ducted (High-static))	COP at 5°F at Maximum Capacity ⁴		1.87 // 1.81 // 1.75 1.81 // 1.75	
	ENERGY STAR® Certified		No // No // No No // No	
	Electrical	Electrical Power Requirements	Voltage, Phase, Frequency	208/230, 1, 60
		Guaranteed Voltage Range	V AC	187-253
		Voltage: Indoor - Outdoor, S1-S2	V AC	208/230
		Voltage: Indoor - Outdoor, S2-S3	V DC	24
Short-circuit Current Rating (SCCR)		kA	5	
Recommended Fuse/Breaker Size		A	25	
Recommended Wire Size (Indoor - Outdoor)		AWG	14	
Minimum Circuit Ampacity		A	22.1	
Maximum Overcurrent Protection		A	25	
Fan Motor Full Load Amperage		A	2.43	
Outdoor unit	Airflow Rate (Cooling / Heating)	CFM	2,133 / 2,243	
	Refrigerant Control		LEV	
	Defrost Method		Reverse Cycle	
	Heat Exchanger Type		Plate Fin Coil	
	Heat Exchanger Coating		Blue Fin Coating	
	Sound Pressure Level, Cooling ¹	dB(A)	52	
	Sound Pressure Level, Heating ²	dB(A)	56	
	Compressor Type		DC INVERTER-driven Twin Rotary	
	Compressor Model		SNB220FCGMC	
	Compressor Rated Load Amps	A	12	
	Compressor Locked Rotor Amps	A	13.7	
	Compressor Oil Type // Charge	oz.	FV50S // 23.7	
	Base Pan Heater		Optional	
	Unit Dimensions	W: In. [mm]		37-13/32 [950]
		D: In. [mm]		13 [330]
		H: In. [mm]		31-11/32 [796]
	Package Dimensions	W: In. [mm]		41-11/32 [1,050]
		D: In. [mm]		17-5/16 [440]
		H: In. [mm]		38-31/32 [990]
	Unit Weight	Lbs.[kg]		142 [64.3]
Package Weight	Lbs.[kg]		174 [78.9]	
Outdoor unit operating temperature range	Cooling Intake Air Temp (Maximum / Minimum ^A)	°FDB	115 / 14	
	Cooling Thermal Lock-out / Re-start Temperatures	°FDB	10.4 / 14	
	Heating Intake Air Temp (Maximum / Minimum)	°FWB	65 / 5	
	Heating Thermal Lock-out / Re-start Temperatures	°FDB	1.4 / 5	

NOTES:

AHRI Rated Conditions ¹Cooling (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB
 (Rated data is determined at a fixed compressor speed) ²Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB
³Heating at 17°F (Indoor // Outdoor) °F 70 DB, 60 WB // 17 DB, 15 WB

Conditions ⁴Heating at 5°F (Indoor // Outdoor) °F 70 DB, 60 WB // 5 DB, 4 WB

*Applications should be restricted to comfort cooling only; equipment cooling applications are not recommended for low ambient temperature conditions.

^A 5°F DB - 115°F DB when optional wind baffles are installed

For actual capacity performance based on indoor unit type and number of indoor units connected, please refer to MXZ Operational Performance.

Although the maximum connectable capacity is 130%, the outdoor unit cannot provide more than 100% of the rated capacity. Please utilize this over capacity capability for load shedding or applications where it is known that all connected units will NOT be operating at the same time.

Low, mid and high external static pressure tests conducted at 0.1, 0.3 and 0.5 in.w.g. respectively, according to AHRI 210/240. The external static pressures utilized have no bearing on the capabilities of the indoor unit; please refer to the indoor unit manual to select the correct external static pressure setting for the application.

SPECIFICATIONS: MXZ-3C30NA4

	Type		R410A
Refrigerant	Pre-Charged Refrigerant Amount	Lbs, oz	6.0, 13.0
	Maximum Pre-Charged Piping Length	Ft. [m]	98.0 [30.0]
	Additional Refrigerant Charge Per Additional Piping Length	oz./Ft. [g/m]	0.216 [20]
Indoor unit connection	Maximum Number of Connected IDU		3
	Minimum Number of Connected IDU		2
	Minimum connected capacity	BTU/H	12,000
	Maximum connected capacity	BTU/H	36,000
Piping	Liquid Pipe Size O.D. (Flared)	In.[mm]	A,B,C: 1/4 [A,B,C: 6.35]
	Gas Pipe Size O.D. (Flared)	In.[mm]	A: 1/2; B,C: 3/8 [A: 12.72; B,C: 9.52]
	Total Piping Length	Ft. [m]	230 [70]
	Maximum Height Difference, ODU above IDU	Ft. [m]	49 [15]
	Maximum Height Difference, ODU below IDU	Ft. [m]	49 [15]
	Farthest Piping Length from ODU to IDU	Ft. [m]	82 [25]
	Maximum Number of Bends for IDU		70

NOTES:

AHRI Rated Conditions ¹Cooling (Indoor // Outdoor) °F 80 DB, 67 WB // 95 DB, 75 WB
 (Rated data is determined at a fixed compressor speed) ²Heating at 47°F (Indoor // Outdoor) °F 70 DB, 60 WB // 47 DB, 43 WB
³Heating at 17°F (Indoor // Outdoor) °F 70 DB, 60 WB // 17 DB, 15 WB

Conditions ⁴Heating at 5°F (Indoor // Outdoor) °F 70 DB, 60 WB // 5 DB, 4 WB

¹Applications should be restricted to comfort cooling only; equipment cooling applications are not recommended for low ambient temperature conditions.
⁴A 5°F DB - 115°F DB when optional wind baffles are installed

For actual capacity performance based on indoor unit type and number of indoor units connected, please refer to MXZ Operational Performance. Although the maximum connectable capacity is 130%, the outdoor unit cannot provide more than 100% of the rated capacity. Please utilize this over capacity capability for load shedding or applications where it is known that all connected units will NOT be operating at the same time.


Low, mid and high external static pressure tests conducted at 0.1, 0.3 and 0.5 in.w.g. respectively, according to AHRI 210/240. The external static pressures utilized have no bearing on the capabilities of the indoor unit; please refer to the indoor unit manual to select the correct external static pressure setting for the application.

OUTDOOR UNIT ACCESSORIES: MXZ-3C30NA4


Air Outlet Guide	Air Outlet Guide (1 Piece)	PAC-SH96SG-E
Ball Valve	Refrigeration Ball Valve - 1/2"	BV12FFSI2
	Refrigeration Ball Valve - 1/4"	BV14FFSI2
	Refrigeration Ball Valve - 3/8"	BV38FFSI2
	Refrigeration Ball Valve - 5/8"	BV58FFSI2
Control Wire	M-Net Control Wire, 1,000' Roll (16-AWG, Standard, Twisted Pair, Shielded, Jacketed- Plenum rated)	CW162S-1000
	M-Net Control Wire, 250' Roll (16-AWG, Standard, Twisted Pair, Shielded, Jacketed- Plenum rated)	CW162S-250
Drain Socket	Drain Socket	PAC-SG60DS-E
Hail Guards	Hail Guard	HG-A9
M-NET Converter	M-NET Converter	PAC-IF01MNT-E
Mini-Split Wire	14 Gauge, 4 wire MiniSplit Cable—250 ft. roll	S144-250
	14 Gauge, 4 wire MiniSplit Cable—250 ft. roll	SW144-250
	14 Gauge, 4 wire MiniSplit Cable—50 ft. roll	S144-50
	14 Gauge, 4 wire MiniSplit Cable—50 ft. roll	SW144-50
	16 Gauge, 4 wire MiniSplit Cable—250 ft. roll	S164-250
	16 Gauge, 4 wire MiniSplit Cable—250 ft. roll	SW164-250
	16 Gauge, 4 wire MiniSplit Cable—50 ft. roll	S164-50
	16 Gauge, 4 wire MiniSplit Cable—50 ft. roll	SW164-50
Mounting Pad	Condensing Unit Mounting Pad: 16" x 36" x 3"	ULTRILITE1
	Outdoor Unit 3-1/4 inch Mounting Base (Pair) - Plastic	DSD-400P
Port Adaptor	Adaptor: 1/2" x 3/8"	MAC-A455JP-E
	Adaptor: 1/2" x 5/8"	MAC-A456JP-E
	Adaptor: 3/8" x 1/2"	MAC-A454JP-E
	Adaptor: 3/8" x 5/8"	PAC-SG76RJ-E
Stand	18" Single Fan Stand	QSMS1801M
	24" Single Fan Stand	QSMS2401M
	Condenser Wall Bracket	QSWB2000M-1
	Condenser Wall Bracket - Stainless Steel Finish	QSWBSS
	Outdoor Unit Stand — 12" High	QSMS1201M

OUTDOOR UNIT DIMENSIONS: MXZ-3C30NA4



Unit: inch (mm)



1.FREE SPACE



2.SERVICE SPACE



1340 Satellite Boulevard Suwanee, GA 30024
 Toll Free: 800-433-4822 www.mehvac.com