



Job Name: \_\_\_\_\_

Job Location: \_\_\_\_\_

Contractor: \_\_\_\_\_

Engineer: \_\_\_\_\_

Approval: \_\_\_\_\_

# Leak-Lock® High Strength Pipe Thread Sealant

### Design Features:

- Original Blue Leak-Lock
- Solvent: Ethanol and Isopropanol
- Non-Toxic

### Operating Specifications:

**Temperature:** - 200° to +400°F  
**Pressure:** Full Vacuum to 10,000 psi  
**Viscosity:** 25,000 - 100,000 CPS  
**Consistency:** Flowable Paste

**Use:** Can be used on all metal and plastic materials, including but not limited to: aluminum, aluminum alloys, brass, bronze, cast irons, copper, copper alloys, magnesium, magnesium alloys, carbon steels, stainless steels, galvanized surfaces, PVC, CPVC, ABS, fiberglass, black polypropylene, and kynar. Should be applied to threaded joints, flanged joints, gasket surfaces and all matting where fluid-tight seal is required.



Set Time	
Pipe Size	Time
0 to 1/2"	1 to 2 hours
1/2" to 1-1/2"	4 to 6 hours
2" to 4"	Over Night

Varies with ambient temperature.

W-R#	Description	Weight	Min	Box
1014002	1.3 oz. Tube	.086 lbs.	12	12
1014004	4 oz. Bottle	.377 lbs.	12	12
1014006	16 oz. Bottle	1.49 lbs.	12	12

\*Not Recommended For Use with Alcohol.