

SUBMITTAL SHEET

JOB NAME		ITEM TAG	
JOB LOCATION		PART NUMBER	
CONTRACTOR	DATE		
ENGINEER APPROVAL	DATE		

HOSE BIBB VACUUM BREAKER

T-553 / T-553C

Female x male garden hose thread connections

Durable forged brass construction

Automatic vacuum interruption prevents backsiphonage

Breakaway set screw for tamper-resistant installation

Available in plain or chrome plated finishes

Not for continuous pressure installations

Working Pressure, Non-Shock (PSI)

CWP: Max 125

Saturated Steam: Not suitable for steam service Maximum service temperature: 180 deg. F

- Certified to ASSE Standard 1011
- Certified to CSA Standard B64.2
- UPC / IAPMO approved









M	MATERIAL SPECIFICATION					
PART		MATERIAL	SPECIFICATION			
1	Body	Forged brass	JIS 3605 Alloy			
2	Washer	Neoprene	Commercial grade 55			
3	Piston seal retainer	Acetal resin	FM090 Acetal copolymer (POM)			
4	Piston seal	NBR (Nitrile) rubber	Commercial grade			
5	Piston	Acetal resin	FM090 Acetal copolymer (POM)			
6	Piston Spring	Stainless steel	AISI 304			
7	Setscrew	Chrome plated mild carbon steel	AISI 12L14 (ASTM A108)			

DIMENSIONS				
Size	Α	В		
3/4"	1.25	1.26		



