



Job Name: \_\_\_\_\_  
 Job Location: \_\_\_\_\_  
 Contractor: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Approval: \_\_\_\_\_

## Drain-King® Drain Cleaners

### Instructions:

- 1) Connect Drain-King to hose.
- 2) Insert Drain-King completely into drain, as far as possible.
- 3) Turn on cold water slowly to full force to clear drain.  
 DO NOT USE HOT WATER. Drain-King will expand and lock itself inside pipe. Powerful pulsing jets of water will loosen and flush blockage.
- 4) To remove: turn off water and loosen hose coupling at faucet. Drain-King will deflate and can be removed from the pipe.

**Recommended Water Pressure:** 40 to 80 psi.

**Note:** The most efficient way to clear most drains is through the clean out-plug on the outside of your home, if water comes out, you should enter at this point. If there is no water then enter through the fixture.



Material Specifications		
No.	Part	Material
1	Hose Connection	Brass
2	Inlet	BP Die Cast
3	Body	Rubber
4	Outlet	BP Die Cast
	Washer	Rubber
	Flow Restrictor	Plastic

W-R#	Size	GT#	Weight
1821000	1" to 2"	501	.155 lbs.
1821002	1-1/2" to 3"	186	.225 lbs.
1821003	3" to 4"	H34	.460 lbs.
1821004	3" to 6"	750	.720 lbs.

DO NOT use in toilets, half in and half out pipes, or where chemicals are present.  
 Made in the USA. 1 Year Warranty.