


MINI-SPLIT PUMP KITS

Continued

White Series



Mounts directly below evaporator, quick installation

Code	Universal Voltage	Power Supply	Power Consumption	Ctn. Wt.	Qty.
83939	(ASP-MW-UNI)	100-250 VAC	.11-.18A 16W	2	1
Accessory					
83933	Ivory Cover			2	1



FEATURES

- Surface mounts below evaporator, at either end
- Crisp white color and slim profile complement any evaporator. Additional colors available (contact RectorSeal®)
- Resilient mounting minimizes vibration & noise
- Cleanable replaceable plastic filter cartridge accepts water treatment tablet
- Accepts standard 5/8" drain hose from any mini-split
- Extra large reservoir capacity minimize pump operation
- All components clip apart for easy disassembly without tools
- Fully potted electronics*

- No breather tube required
- No need to disturb evaporator to clean filter, reservoir clips out from front for easy removal and replacement
- 3A N/C dry contacts rated @ 5A inductive @ 230V AC

Specifications:

Duty Cycle: Continuous

Capacity:


Up to 30,000 BTU/hr.
3.2 GPH @ zero head,
0.8 GPH @ 33ft head

Maximum head: 33ft

Maximum Water Temp: 104° F

Sound level: 25dB(A)

TYPICAL PUMP LOCATIONS



Pump Dimensions:
L-7 1/8" x H-4 1/2" x W-2"

