υροποι

Uponor AquaPEX red coils

Project information		
Job name:	Location:	
Engineer:	Date submitted:	
Contractor:	Submitted by:	
Manufacturer's representative:	Approved by:	

rechnical data	
Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Product information and application use

Uponor AquaPEX® red tubing is used primarily for hot potable-water distribution, but can also be used in radiant heating and cooling systems containing no ferrous corrodible components or where ferrous components are isolated from the tubing.



Part name	Part no.	Inner diameter coil [inch]	Outer diameter coil [inch]	Coil width [inch]	Inner diameter pipe [inch]	Outer diameter pipe [inch]	Weight per UOM [lbs/UOM]
1/2" Uponor AquaPEX Red, 100-ft. coil	F2040500	15.75	23.5	3.5	0.475	0.625	6
3/4" Uponor AquaPEX Red, 100-ft. coil	F2040750	15.75	32	3	0.671	0.875	10
1" Uponor AquaPEX Red, 100-ft. coil	F2041000	22.7	32	6.5	0.862	1.125	20
1/2" Uponor AquaPEX Red, 300-ft. coil	F2060500	19.7	32	4	0.475	0.625	18
3/4" Uponor AquaPEX Red, 300-ft. coil	F2060750	22	32	8	0.671	0.875	34
1" Uponor AquaPEX Red, 300-ft. coil	F2061000	22.7	32	16	0.862	1.125	56
1/2" Uponor AquaPEX Red, 1,000-ft. coil	F2120500	15.75	32	10.5	0.475	0.625	54

Installation

Approved fitting system is ProPEX®1. Refer to the Uponor ProPEX Connections Instructional Guide, the Uponor Professional Plumbing Installation Guide or the Uponor Piping Pocket Guide for more information.

Related applications

PEX-a Plumbing Systems

Codes	Standards	Listings
IMC UPC IBC IRC NBC of Canada IPC UFGS NPC of Canada UMC NSPC	E2023JASTM E814/ULC S115JASTM E877JCSA B137 5JULC	
Footnotes		Contact information

	Uponor Inc.	Uponor Ltd.
	5925 148th Street West	6510 Kennedy Road
* Some SKUs in this family have additional codes, standards, or listings. Please see uponor.com for	Apple Valley, MN 55124	Mississauga, ON L5T 2X4
complete information.	T 800.321.4739	T 888.594.7726
	F 952.891.2008	F 800.638.9517
complete information.		