

Tubing



ViegaPEX Ultra tubing

- PEX
- Coil

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5001

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	red	5.000	1	32101 ¹	1
3/8	500	red	21.000	1	32105 ¹	1
3/8	1000	red	42.000	1	32100	1
1/2	100	red	5.800	1	32121 ¹	1
1/2	300	red	17.100	1	32123 ¹	1
1/2	500	red	28.000	1	32125 ¹	1
1/2	1000	red	58.000	1	32120	1
3/4	100	red	11.000	1	32141 ¹	1
3/4	300	red	32.100	1	32143 ¹	1
3/4	500	red	53.000	1	32145 ¹	1
1	100	red	16.900	1	33323 ¹	1
1	300	red	50.700	1	32163	1
1	500	red	88.000	1	32165	1

¹ center pull coil



ViegaPEX Ultra tubing

- PEX
- Straight length

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5001.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	red	0.540	50	33272	1
1/2	20	red	1.060	50	33120	1
3/4	10	red	1.020	25	33275	1
3/4	20	red	2.040	25	33145	1
1	20	red	3.420	5	33270	1



ViegaPEX Ultra tubing

- PEX
- Coil

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5002

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
3/8	100	blue	5.000	1	32201 ¹	1
3/8	500	blue	21.000	1	32205 ¹	1
3/8	1000	blue	42.000	1	32200	1
1/2	100	blue	5.300	1	32221 ¹	1
1/2	300	blue	17.100	1	32223 ¹	1
1/2	500	blue	26.500	1	32225 ¹	1
1/2	1000	blue	55.000	1	32220	1
3/4	100	blue	11.000	1	32241 ¹	1
3/4	300	blue	32.100	1	32243 ¹	1
3/4	500	blue	53.000	1	32245 ¹	1
1	100	blue	17.000	1	32266	1
1	300	blue	50.700	1	32263	1
1	500	blue	88.000	1	32265	1

¹ center pull coil



ViegaPEX Ultra tubing

- PEX
- Straight length


Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5002.5

d	L [ft]	Version	Wt [lb]	Quantity	Part No	DG
1/2	10	blue	0.540	50	33274	1
1/2	20	blue	1.060	50	33240	1
3/4	10	blue	1.020	25	33277	1
3/4	20	blue	2.040	25	33265	1
1	20	blue	3.420	5	33271	1



ViegaPEX Ultra tubing

- For installation between studs
- PEX
- ManaPac

components

Recycled plastic reels

Technical Data

PEX designation code 5306
UV resistance 6 months

ASTM F876, ASTM F877

Model V5004

d	L [ft]	Reel(s)	Version	Wt [lb]	Quantity	Part No	DG
3/8	500	2	red/blue	58.000	1	32300 ¹	1
3/8	500	1	blue	28.000	1	32905	1
3/8	500	1	red	28.000	1	32805	1
1/2	300	2	red/blue	48.000	1	32326 ¹	1
1/2	300	1	blue	23.100	1	32923	1
1/2	300	1	red	23.100	1	32823	1

¹ Available while supplies last



Viega MiniBloc zoning manifold

Smart Connect feature

- For combination systems
- Press connection
- Blue color coded ports for cold water

components

¼ turn valves, T-handle valve key, optional red valve caps

Note

Does not include supply connections

Model V5650

Adapter	Port(s)	d	Wt [lb]	Quantity	Part No	DG
polymer	3	½	1.804	1	49033	2
polymer	4	½	2.007	1	49043	2
polymer	6	½	2.456	1	49063	2
polymer	8	½	3.337	1	49083	2



Viega MiniBloc zoning manifold

Smart Connect feature

- For combination systems
- Press connection
- Color coded ports for hot and cold water

components

¼ turn valves, T-handle valve key

Note

Does not include supply connections

Model V5660

Adapter	Port(s)	d	d hot	cold	Wt [lb]	Quantity	Part No	DG
polymer	5	½	2	3	2.189	1	49453	2
polymer	7	½	3	4	3.130	1	49473	2
polymer	10	½	4	6	3.801	1	49410	2



Viega PEX Press port adapter

Smart Connect feature

- For connecting distribution lines to Viega ManaBloc and Viega MiniBloc
- Polymer
- Press connection, Viega ManaBloc port connection

Model V5613.1

P	Port	Wt [lb]	Quantity	Part No	DG
¾	½	0.047	6	49224	2
½	½	0.050	6	49234	2



Viega PEX Press port adapter

Zero Lead

- For connecting distribution lines to Viega ManaBloc and Viega MiniBloc
- Bronze
- Press connection, Viega ManaBloc port connection

Model 2877.3ZL

P	Port	Wt [lb]	Quantity	Part No	DG
¾	½	0.095	6	96101	2
½	½	0.102	6	96120	2



Viega PEX Press supply adapter

Smart Connect feature

- For connecting PEX supply lines to Viega ManaBloc and Viega MiniBloc
- Polymer
- Press connection, Viega ManaBloc supply connection

Model V5613.2

P	Supply	Wt [lb]	Quantity	Part No	DG
¾	1	0.098	5	49414	2
1	1	0.118	5	49416	2