

A3C • A4C



Clear Heat Shrink Splice Kits

APPLICATIONS

Specifically designed with 3M for use in the groundwater industry, A3C and A4C splice kits form a permanent, waterproof barrier for uncomplicated and effective submersible pump wiring and installation. These kits are made to accommodate 3 or 4 leads ranging in size from #14 AWG to #10 AWG.

A3C kit contains components for 3 leads.

A4C kit contains components for 4 leads.

COMPONENTS

A3C contains 3 pieces of tubing and 3 connectors in each kit.

A4C contains 4 pieces of tubing and 4 connectors in each kit.

Advance E&I ATHSPC Clear Heat Shrink Tubing

- 3" Clear Tubing Made in the USA by 3M
- Electron beam cross-linking transforms the polyolefin tubing into an entirely new class of high temperature material with significantly improved properties and a 3:1 shrink ratio
- Dual-wall construction provides abrasion resistance and moisture-seal protection
- Offers the advantage of integral, adhesive-lined construction
- Withstands temperatures of -67 to 230 degrees F (-55 to 110 degrees C)
- Rated for 600V applications
- CSA Certified and RoHS 2011/65/EU Compliant

B1210 Non-Insulated Seamless Butt Connector

- Seamless Non-Insulated Butt Connector Made in the USA by 3M
- Wire size range of #14 AWG - #10 AWG
- Made of electrolytic copper for good conductivity and has tin plating for corrosion resistance
- Built in wire stop for correct wire positioning
- Withstands temperatures of -40 to 221 degrees F (-40 to 105 degrees C)
- Rated for 600V applications
- UL Listed, CSA Certified and RoHS 2011/65/EU Compliant

