

**PS5266-X, CR5266-X, PS5269-X, CR5269-X, PS5366-X, PS5369-X, PS5666-X, PS5669-X, PS5466-X, PS5469-X**

**Rugged construction for the toughest environments.**

**B**uilt to last with clear thermoplastic terminal chambers for assured terminations, industrial-strength brass alloy blades and contacts that reduce heat rise, sturdy external cord grips with offset jaw clamping, and tough nylon housings to resist impacts and chemicals. Internal dust shield maintains contaminant-free wiring chamber. Easy to install: tri-drive terminal and assembly screws come backed-out and ready-to-wire. Internal dust shield maintains contaminant-free wiring chamber. Easy to install: tri-drive terminal and assembly screws come backed-out and ready-to-wire, and all three terminal screws are on the same plane for fast termination.



**Features & Benefits**

**Quick-thread assembly screws** and cord grip screws come backed-out, ready-to-wire.

**Industrial-strength, brass alloy plug blades and connector contacts** resist heat rise, provide excellent conductivity. Ground pin is reinforced for added strength and safety.

**See-through, thermoplastic terminal chamber** for clear view of terminals and wire connections.

**Color-coded terminal screws** are positioned on same plane and backed-out for fast installation.

**Tapered wire wells** guide conductors into captivated, staked clamping nuts.

**Double-wipe, firm-grip ground contact and triple-wipe power contacts** guarantee a superior connection.

**Housing is keyed** for fast alignment with terminal section.

**Rugged external two-piece cord grip** provides uniform pressure for superior retention of conductors.

**Chemical- and impact-resistant nylon housing** features horizontal, easy-grip ribs on back body.

**Internal dust shield** keeps terminals free of contaminants.

**PS5266-X and PS5269-X**

**Recessed cord-grip screw** reduces screwdriver slippage, improves safety.

**Field Uses/Vertical Markets**

- Industrial
- Health Care
- Education
- Institutional
- Retail
- Office
- Hospitality/Lodging
- Multiple Dwelling



Pass & Seymour

# Straight Blade Plugs & Connectors Extra-Hard Use

## 15 & 20A, 125 & 250V

### Ordering Information

Catalog Number	Rating A. V.	Description/Color	Cord Diameter	NEMA Config. No.
<b>Plugs &amp; Connectors</b>				
PS5266-X	15 125	Plug, Black & White	.230"-.690"	5-15P
PS5266-XGRY	15 125	Plug, Black & Gray	.230"-.690"	5-15P
PS5266-XBK	15 125	Plug, Black	.230"-.690"	5-15P
CR5266-X	15 125	Plug, Corrosion-Resistant, Yellow & White	.230"-.690"	5-15P
PS5269-X	15 125	Connector, Black & White	.230"-.690"	5-15R
PS5269-XGRY	15 125	Connector, Black & Gray	.230"-.690"	5-15R
PS5269-XBK	15 125	Connector, Black	.230"-.690"	5-15R
CR5269-X	15 125	Connector, Corrosion-Resistant, Yellow & White	.230"-.690"	5-15R
PS5366-X	20 125	Plug, Black & White	.230"-.690"	5-20P
PS5369-X	20 125	Connector, Black & White	.230"-.690"	5-20R
PS5666-X	15 250	Plug, Black & White	.230"-.690"	6-15P
PS5669-X	15 250	Connector, Black & White	.230"-.690"	6-15R
PS5466-X	20 250	Plug, Black & White	.230"-.690"	6-20P
PS5469-X	20 250	Connector, Black & White	.230"-.690"	6-20R



NEMA  
5-15R



NEMA  
5-15P



NEMA  
6-15R



NEMA  
6-15P



NEMA  
5-20R



NEMA  
5-20P



NEMA  
6-20R



NEMA  
6-20P

For more information on these and other P&S products refer to our Catalog or visit our web site.

SF501R2 — Updated March 2008 — For latest specs visit [www.legrand.us/passandseymour](http://www.legrand.us/passandseymour)