



Campbell

Installation Accessories

PRESSURE GAUGE



part	face diam.	range	connection	pcs/ctn	master ctn
PG1T-NL	2	0-100	1/4 lm	1	100
PG1T-SS	2	0-100	1/4 lm	1	100
PG1 1/8T-NL	2	0-100	1/8 lm	1	Bulk
PG2T-NL	2	0-200	1/4 lm	1	100
PG2T-SS	2	0-200	1/4 lm	1	100
PG3T-NL	2	0-30	1/4 lm	1	100
PG4T-NL	2	0-60	1/4 lm	1	100
PG5T-NL	2	0-160	1/4 lm	1	Bulk
PG6T-NL	2	0-300	1/4 lm	1	Bulk
PG9T-NL	2-1/2	0-30	1/4 lm	1	Bulk
PG11T-NL	2-1/2	0-100	1/4 lm	1	Bulk
PG13T-NL	2-1/2	0-200	1/4 lm	1	Bulk
PG14T-NL	2-1/2	0-300	1/4 lm	1	Bulk
PG20T-NL	2	0-15	1/4 lm	1	Bulk
PGV-NL	2	30VAC	1/4 lm	1	100
PGCBM-0-NL	2	0-100	1/8 cbm	1	100
PGCBM-1-NL	2	0-100	1/4 cbm	1	100
PGCBM-1-SS	2	0-100	1/4 cbm	1	100
PGP1-NL	2	0-100	1/4 lm	1	100

All gauges have steel cases and brass (NL) or stainless steel (SS) connections (except PGP1 which has a plastic case). Gauge lenses are glass or polycarbonate.


PRESSURE GAUGE (liquid-filled)



PG1T-L-NL	2	0-100	1/4 lm	1	100
PG3T-L-NL	2	0-30	1/4 lm	1	100
PG10T-L-NL	2-1/2	0-60	1/4 lm	1	50
PG11T-L-NL	2-1/2	0-100	1/4 lm	1	
PG12T-L-NL	2-1/2	0-160	1/4 lm	1	50
PG13T-L-NL	2-1/2	0-200	1/4 lm	1	50
PG14T-L-NL	2-1/2	0-300	1/4 lm	1	50
PG15T-L-NL	2-1/2	0-400	1/4 lm	1	50
PGCBM-1-L-SS	2	0-100	1/4 cbm	1	100
PGVLSS	2	30VAC	1/4 lm	1	100

Glycerine-filled to reduce vibration. Stainless steel case, polycarbonate lens, and brass connection.

TOP GUIDE



part	drop pipe	casing i.d.	pcs/ctn	master ctn
TG4A	1	4	Bulk	-
TG4B	1-1/4	4	Bulk	-
TG4 1/2A	1	4-1/2	Bulk	-
TG4 1/2B	1-1/4	4-1/2	Bulk	-
TG4 1/2T*	1	4-1/2	Bulk	-
TG5A	1	5	Bulk	-
TG5B	1-1/4	5	Bulk	-
TG5 5/8A	1	5-5/8	Bulk	-
TG5 5/8B	1-1/4	5-5/8	Bulk	-
TG5 5/8P**	1	5-5/8	Bulk	-
TG5 5/8T*	1	5-5/8	Bulk	40
TG6A	1	6	Bulk	-
TG8A	1	8	Bulk	-

Made from molded styrene butadiene rubber.

* Imported.

** TG5 5/8P is molded from FDA-approvable PVC

Campbell Manufacturing, LLC
127 East Spring Street
P.O. Box 207
Bechtelsville, PA 19505-9153
800-523-0224, Fax 610-369-3580

All gauges are imported.



PG13T-L-NL

PG11T-NL



PGP1-NL



PG3T-NL

PG1T-NL



PGCBM-1-L-SS



PG1T-L-NL

PG1T-SS



PGCBM-0-NL

