## υροποι

## Ecoflex thermal twin coils

Project Information	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data	
Material	PEX
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)

Product information and application use

Uponor's Ecoflex® Thermal Twin is a pre-insulated pipe system for buried or aboveground commercial and residential hydronic heating and cooling applications. Service pipes are made from durable Engel-method crosslinked polyethylene (PEX-a) tubing, protected by multilayer PEX-foam insulation and covered by a corrugated, waterproof HDPE jacket. Use with Uponor ProPEX® fittings or WIPEX<sup>™</sup> dezincification-resistant (DZR) brass compression fittings.



Part name	Part no.	Inner diameter coil [inch]	Outer diameter coil [inch]	Coil width [inch]	Inner diameter pipe [inch]	Outer diameter pipe [inch]	Weight per UOM [lbs/UOM]
1 1/4" Thermal Twin Jr. with 5.5" Jacket, 600-ft. coil	5025513	5.5	12	5.5	1.054	1.375	1.28
1" Thermal Twin with 6.9" Jacket, 600-ft. coil	5026910	6.9	12	6.9	0.862	1.125	1.3
1 1/4" Thermal Twin with 6.9" Jacket, 500-ft. coil	5026913	6.9	12	6.9	1.054	1.375	1.4
1 1/2" Thermal Twin with 6.9" Jacket, 300-ft. coil	5026915	6.9	12	6.9	1.244	1.625	1.55
2" Thermal Twin with 7.9" Jacket, 300-ft. coil	5027920	7.9	12	7.9	1.629	2.125	2.68
2 1/2" Thermal Twin with 7.9" Jacket, 300-ft. coil	5027925	7.9	12	7.9	2.011	2.625	3.4

## Installation

Install Ecoflex Thermal Twin pre-insulated pipe in buried or aboveground hydronic heating and cooling applications. Ecoflex End Caps are required on all exposed ends of Ecoflex pipes to avoid ground water contamination. For more information, refer to the Uponor Pre-insulated Pipe Systems Design and Installation Manual.

## Related applications

Pre-Insulated Pipe Systems Hydronic Heating and Cooling Systems

Radiant Heating and Cooling Systems

- Permafrost Prevention Systems
- Turf Conditioning Systems
- AquaSAFE™ Fire Safety Systems

Codes	Standards	Listings
UPC IPC NPC of Canada UMC NSPC IMC	ASTM F877 ASTM F1960 CSA B137.5 ASTM F876 NSF-61 ASTM F876 NSF-14	cNSFus-pw cNSFus-rfh U.P.Code
Footnotes		Contact information
Foulintes	Contact information	
	Uponor Inc.	Uponor Ltd.
	5925 148th Street W	/est 6510 Kennedy Road
-	Apple Valley, MN 55	124 Mississauga, ON L5T 2X4
	T 800.321.4739	T 888.594.7726
	F 952.891.2008	F 800.638.9517