

Features

- Vitreous china.
- Elongated bowl.
- Equipped with Sloan FLUSHMATE®- Sloan® Valve Company.
- Polished chrome trip lever.
- Less seat and supply.
- 12" (305 mm) rough-in.
- 1.0 gpf (3.8 lpf).
- 11-1/2" (292 mm) x 9-1/2" (241 mm) water area.
- 30-3/8" (772 mm) x 21-1/4" (540 mm) x 29-3/4" (756 mm).

Recommended Accessories

K-4650 Toilet Seat K-7637 Angle Supply with Stop (single)

Components

Product includes: K-4303 Toilet Bowl K-4484 Toilet Tank Additional included component/s: Tank cover, Trip lever, Bolt cap accessory pack, and Equipped with Sloan FLUSHMATE® – Sloan® Valve Company.





Codes/Standards

ASME A112.19.2/CSA B45.1 DOE - Energy Policy Act 1992 EPA WaterSense[®] California Energy Commission (CEC)

KOHLER® One-Year Limited Warranty

See website for detailed warranty information.

Available Color/Finishes

Color tiles intended for reference only.

Color Code Description

- 96 Biscuit
- 47 Almond
 - 7 Black Black™




Wellworth® Pressure Lite® Toilet K-3531



Wellworth[®]

Pressure Lite® Toilet

K-3531



Technical Information

All product dimensions are nominal.		
Toilet type:	Two-piece	
Bowl shape:	Elongated front	
Flush type:	Pressure Assisted	
Trap passageway:	2-1/4" (57 mm)	
Water surface size:	11-1/2" x 9-1/2" (292 mm x 241 mm)	
Rim to water surface:	5-5/8" (143 mm)	
Rough-in:	12" (305 mm)	
Seat-mounting holes:	5-1/2" (140 mm)	

Fixture Supply Requirements

Min static pressure:	35 psi (241.3 kPa)
Max static pressure:	80 psi (551.6 kPa)

Notes

Install this product according to the installation instructions.

Install this product according to the installation guide.

For back-to-back toilet installations: Use only a 45° double wye fitting.

