υροποι

Uponor AquaPEX white coils with red print

| Project information | |
|--------------------------------|-----------------|
| Job name: | Location: |
| Engineer: | Date submitted: |
| Contractor: | Submitted by: |
| Manufacturer's representative: | Approved by: |
| We also be to also be | |

| roominoal data | | | | | |
|-----------------------------------------|-------------------------------------|--|--|--|--|
| Material | PEX | | | | |
| Temp/pressure ratings | 73 °F (23 °C) at 160 psi (11 bar) | | | | |
| | 180 °F (82 °C) at 100 psi (6.9 bar) | | | | |
| | 200 °F (93 °C) at 80 psi (5.5 bar) | | | | |
| Draduct information and application use | | | | | |

Product information and application

Uponor AquaPEX® white tubing with red print is used primarily in hot potable water distribution systems, but can also be used in radiant heating and cooling systems containing no ferrous corrodible components or where ferrous components are isolated from the tubing



| Part name | Part no. | Inner diameter coil [inch] | Outer diameter coil [inch] | Coil width [inch] | Inner diameter pipe [inch] | Outer diameter pipe [inch] | Weight per UOM [lbs/UOM] |
|-----------------------------------------------------|----------|----------------------------------|----------------------------------|----------------------|----------------------------------|----------------------------------|--------------------------------|
| 1/2" Uponor AquaPEX White, Red Print, 1000-ft. coil | F4220500 | 15.75 | 32 | 10.5 | 0.475 | 0.625 | 54 |
| 1/2" Uponor AquaPEX White, Red Print, 100-ft. coil | F4240500 | 15.75 | 23.5 | 3.5 | 0.475 | 0.625 | 6 |
| 3/4" Uponor AquaPEX White, Red Print, 100-ft. coil | F4240750 | 15.75 | 32 | 3 | 0.671 | 0.875 | 10 |
| 1" Uponor AquaPEX White, Red Print, 100-ft. coil | F4241000 | 22.7 | 32 | 6.5 | 0.862 | 1.125 | 20 |
| 1/2" Uponor AquaPEX White, Red Print, 300-ft. coil | F4260500 | 19.7 | 32 | 4 | 0.475 | 0.625 | 18 |
| 3/4" Uponor AquaPEX White, Red Print, 300-ft. coil | F4260750 | 22 | 32 | 8 | 0.671 | 0.875 | 34 |
| 1" Uponor AquaPEX White, Red Print, 300-ft. coil | F4261000 | 22.7 | 32 | 16 | 0.862 | 1.125 | 56 |
| | | | | | | | |

Installation

Approved fitting system is ProPEX®1. Refer to the Uponor ProPEX Connections Instructional Guide, the Uponor Professional Plumbing Installation Guide or the Uponor Piping Pocket Guide for more information.

Related applications

PEX-a Plumbing Systems

Radiant Heating and Cooling Systems

Apple Valley, MN 55124

T 800.321.4739

F 952.891.2008

| Codes | Standards | Listings | | |
|------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|--|--|
| IMC UPC IBC IRC NBC of Canada IPC UFGS NPC of Canada UMC NSPC | ASTM F1960 ASTM E119/UL 263 ASTM F876 ASTM E84 ASTM F2023 ASTM E814/ULC S115 ASTM F877 CSA B137.5 ULC S102.2 CSA B214 NSF-61 ULC S101 NSF-14 | IAPMO-ES ICC-ES-PMG cNSFus-pw CCMC PPI TR- 4 CSA UL U.P.Code cQAlus P321 HUD MR 1269 BMEC | | |
| Footnotes | | Contact information | | |
| | Uponor Inc. 5925 148th Street V | Uponor Ltd. Vest 6510 Kennedy Road | | |

| © 2023 Uponor North America. | All Rights Reserved |
|------------------------------|---------------------|
|------------------------------|---------------------|

Mississauga, ON L5T 2X4

T 888.594.7726

F 800.638.9517