# υροποι

## QS-style compression manifold fitting assemblies

Flood montation	
Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data	
Material	Brass
Temp/pressure ratings	73 °F (23 °C) at 160 psi (11 bar)
	180 °F (82 °C) at 100 psi (6.9 bar)
	200 °F (93 °C) at 80 psi (5.5 bar)
Prop 65 label required?	Yes

#### Product information and application use

The Uponor R20 Compression Fitting Assembly threads onto manifold loop outlets. This R20 QS (Quick Seal) compression fitting connects Wirsbo hePEX<sup>TM</sup> or Uponor AquaPEX® tubing to the manifold in radiant heating applications and is designed for 5 /16",  $\frac{3}{6}$ ",  $\frac{1}{2}$ " or  $\frac{5}{6}$ " tubing. The R25 QS compression fitting does not directly thread onto the manifold, but onto other R25 connections, and is designed for use with  $\frac{5}{6}$ " and  $\frac{3}{4}$ " tubing only.



Part name	Part no.	A [inch]	B [inch]	C [inch]	D [inch]	Weight per UOM [lbs/UOM]	End Type 1	End Type 2
5/16" QS-style Compression Fitting Assembly, R20 thread	A4020313	1.372	1.187	1.057	-	0.26	QS 5/16"	ISO 228-G 3/4"
3/8" QS-style Compression Fitting Assembly, R20 thread	A4020375	1.372	1.187	1.004	0.95	0.23	QS 3/8"	ISO 228-G 3/4"
1/2" QS-style Compression Fitting Assembly, R20 thread	A4020500	1.372	1.187	1.004	0.95	0.21	QS 1/2"	ISO 228-G 3/4"
5/8" QS-style Compression Fitting Assembly, R20 thread	A4020625	1.372	1.187	1.004	0.95	0.19	QS 5/8"	ISO 228-G 3/4"
3/4" QS-style Compression Fitting Assembly, R25 thread	A4020750	1.66	1.5	1.099	1.18	0.33	QS 3/4"	ISO 228-G 1"
Replacement O-ring for insert (R25)	A4021000	0.934	0.934	0.07	-	0	-	-
Replacement O-ring for insert (R20)	A4021116	0.621	0.621	0.07	-	0	-	-
5/8" QS-style Compression Fitting Assembly, R25 thread	A4030625	1.729	1.5	1.064	1.18	0.4	QS 5/8"	ISO 228-G 1"

#### Installation The R20-threaded Compression Fitting connects to Uponor manifold loop outlets. The compression end enables direct connection to Wirsbo hePEX tubing. Use the R25-threaded Compression Fitting for other R25 connections. For more information, refer to the Radiant Floor Heating Installation Handbook.

### Related applications

Radiant Heating and Cooling Systems

Permafrost Protection Systems

Turf Conditioning Systems

Codes	Standards	Listings		
IMC IRC NBC of Canada UMC	CSA B137.5 R32:	cNSFus-rfh ICC-ES-PMG 1012		
Footno	ites	Contact i	nformation	
		Uponor Inc.	Uponor Ltd.	
<ul> <li>* Some SKUs in this family have additional codes, standards, or listings. Please see uponor.com for complete information.</li> </ul>		5925 148th Street West	6510 Kennedy Road	
		Apple Valley, MN 55124	Mississauga, ON L5T 2X4	
		T 800.321.4739	T 888.594.7726	
		F 952.891.2008	F 800.638.9517	