

# Wirsbo hePEX™ Tubing, 2½" to 4" Coils

Submittal Information  
Revision G: Dec. 7, 2015

## Project Information

Job Name:	
Location:	Part No. Ordered:
Engineer:	Date Submitted:
Contractor:	Submitted By:
Manufacturer's Representative:	Approved By:

## Technical Data

Material:	Crosslinked polyethylene PEX-a Engel Method
Thermal Conductivity:	0.22 Btu.ft/sq.ft.hr.degF
Standard Grade	200°F at 80 psi (93°C at 5.51 bar)
Hydrostatic Ratings (PPI):	180°F at 100 psi (82°C at 6.89 bar) 73.4°F at 160 psi (23°C at 11.03 bar)
Linear Expansion Rate:	1.1"/10°F per 100 ft. (27.94mm/5.56°C per 30.48m)



## Product Information and Application Use

Wirsbo hePEX™ tubing is used for closed-loop heating and cooling applications, including radiant and hydronic distribution. It has an EVOH oxygen diffusion barrier that meets German DIN 4726/9. These larger-sized products are designed for commercial projects or other custom-designed applications.

✓ Description	Part Number	Tube ID	Tube OD	Weight
2½" Wirsbo hePEX, 100-ft. coil	A1142500	2.011"	2.625"	92.20 lbs.
2½" Wirsbo hePEX, 300-ft. coil	A1252500	2.011"	2.625"	276.56 lbs.
3" Wirsbo hePEX, 100-ft. coil	A1143000	2.400"	3.125"	129.70 lbs.
3" Wirsbo hePEX, 300-ft. coil	A1253000	2.400"	3.125"	389.08 lbs.
3½" Wirsbo hePEX, 100-ft. coil	A1143500	2.784"	3.625"	173.80 lbs.
4" Wirsbo hePEX, 100-ft. coil	A1144000	3.169"	4.125"	225.13 lbs.

## Installation

Use ProPEX® fittings to connect pipe sizes up to 3".<sup>1</sup> Use WIPEX™ fittings for 3½" and 4" pipe. Refer to the Uponor Complete Design Assistance Manual (CDAM) or Hydronic Piping Design Assistance Manual (HPDAM) for additional information.

## Listings<sup>2</sup>

cNSFus-rfh; cNSFus-pw; cQAIus P321; UL; CSA; WH; ETL; PPI TR-4; ICC-ES; CCMC

## Codes

ICC; IPC; IMC; IRC; UPC; UMC; NSPC; HUD; UFGS; NPC of Canada; NBC of Canada; IAPMO

## Standards

ANSI/NSF 14; ANSI/NSF 61; ASTM F876; ASTM F877; ASTM F1960; ASTM F2023; ASTM E84; CAN/ULC S102.2; ASTM E119/UL 263; CAN/ULC S101; ASTM E814/ULC S115; CSA B137.5; CSA B214; DIN 4726/9; AWWA C904<sup>3</sup>

## Related Applications

Radiant Heating and Cooling Systems  
Snow and Ice Melting Systems  
Permafrost Protection Systems  
Turf Conditioning Systems  
Chilled Water Distribution  
Hot Water Distribution

## Contact Information

Uponor, Inc.  
5925 148<sup>th</sup> Street West  
Apple Valley, MN 55124 USA  
Phone: 800.321.4739  
Fax: 952.891.2008  
www.uponorpro.com

Uponor Ltd.  
2000 Argentia Road, Plaza 1, Suite 200  
Mississauga, ON L5N 1W1 CANADA  
Phone: 888.994.7726  
Fax: 800.638.9517  
www.uponorpro.com

<sup>1</sup>ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.

<sup>2</sup>Visit listing agency's website for complete information.

<sup>3</sup>For ¾" to 3" pipe.