

# **Pre-Pressurized Well Tanks**

High Quality. Easy to Install.

The **4Pro Pre-Pressurized Well Tanks** 

deliver reliable performance at an affordable price. All tanks feature 125 PSI working pressure, stainless steel system connection, fresh water Turbulator<sup>®</sup>, heavy duty diaphragm and a 5-Year limited warranty.



## **FEATURING:**

#### **125 PSI Working Pressure**

• Deep drawn steel is double the strength of head-and-shell designs.

## **Stainless Steel System Connection**

 High grade 304L material for longer life in aggressive water conditions.

#### Fresh Water Turbulator®

• Patented technology agitates incoming water to reduce stagnation.

## **Heavy-Duty Diaphragm**

• Pro-grade material for durability.

## **Polypropylene Liner**

 Nonmetallic barrier meets NSF® International Standard 61; no sprayed-on coatings.

#### **Projection-Welded Air Stem**

 Eliminates potential leak paths to maintain precharge. No gaskets or threaded fittings.

## **Welded Steel Base**

 Won't rotate out of position or wobble like some plastic stands or clamp-on metal designs.


#### **Lead Free Construction**

 No brass parts or lead-bearing components.

## **5-Year Warranty**



## **Water System Well Tanks**



SPECIFICATIONS									
Model	Tank Volume (Gallons)	Max. Accept. Factor	A Diameter (Inches)	B Height (Inches)	System Connection (Inches)	System Drawdown (Gallons)			Shipping
						30/50 PSI	40/60 PSI	50/70 PSI	Weight (lbs.)
4PRO4SWT	4.4	.55	11	15	3/4 NPTM	1.4	1.2	1.0	9
4PRO20SWT	20	.57	15	32	1 NPTF	6.2	5.4	4.7	30
4PRO26SWT	26	.44	15	39	1 NPTF	8.0	7.0	6.1	37
4PRO32SWT	32	.35	15	47	1 NPTF	9.9	8.6	7.6	43
4PRO44SWT	44	.77	22	36	1 NPTF	13.6	11.8	10.4	57

Stainless Steel System Connection with Fresh Water Turbulator®

Maximum Operating Temperature: 200°F. Factory Pre-Charge: 38 PSI. Maximum Working Pressure: 125 PSI.



SIZING								
Pump Discharge Rate GPM	Pumps Up To 3/4 hp & 1 Minute Run Time							
(Approx.)	30/50 PSI	40/60 PSI	50/70 PSI					
5	4PRO20SWT	4PRO20SWT	4PRO26SWT					
7	4PRO26SWT	4PRO32SWT	4PRO32SWT					
10	4PRO32SWT	4PRO44SWT	4PRO44SWT					
12	4PRO44SWT	-	-					









MC10365 (07/25)