

### Features

- Trim plate includes temperature control knob with integrated adjustable high-temperature limit stop and shower outlet on/off buttons
- When pressed once, shower outlet turns on and button pops out, becoming a knob for water flow adjustment
- When pressed back in, water turns off and outlet button aligns with control plate surface; flow setting remains intact
- High-temperature limit setting for added safety
- Low-profile design with easy-to-clean water-resistant casing
- Requires two-port thermostatic valve with integral volume control (sold separately)
- Handles up to 8 gpm (30.3 lpm) flow capacity (rate may vary by installation)



### Installation

- Mounts on finished wall surface

### Required Products/Accessories

P34723-00 Mechanical showering two-port thermostatic valve with integrated volume control

### Codes/Standards









ASME A112.18.1/CSA B125.1

### KALLISTA® Five-Year Limited Warranty

See website for detailed warranty information.




### Available Colors/Finishes

*Color tiles intended for reference only.*

Color	Code	Description
	CP	Polished Chrome
	BL	Matte Black
	BN	Brushed Nickel
	BAF	Brushed French Gold
	PB	Polished Brass
	SN	Polished Nickel
	BV	Brushed Bronze
	AF	French Gold

# KALLISTA

Foundations by KALLISTA  
Mechanical showering two-outlet thermostatic  
control panel  
P34719-00



## Technical Information

All product dimensions are nominal.

## Notes

Install this product according to the installation instructions.