

Concealed flat cover plates

Project information

Job name:	Location:
Engineer:	Date submitted:
Contractor:	Submitted by:
Manufacturer's representative:	Approved by:

Technical data

Prop 65 label required? Yes

Product information and application use

Concealed flat cover plates easily slide onto flat concealed sprinklers for a finished appearance. The flat cover plate completely hides the sprinkler from view. All cover plates detach from the sprinkler assembly when temperatures reach 135°F (57.2°C) to 140°F (60°C).



Part name	Part no.	Weight per UOM [lbs/UOM]
Concealed Flat Cover Plate for HSW, White, (HSW style only)	Q70640HW	0.13
Concealed Flat Cover Plate for 162F LF RC-RES Sprinkler, White, 3 1/4	Q70749WH	0.1

Installation

Do not store cover plates in areas where the ambient temperature will exceed 100°F (37.7°C). Cover plates must be used with LF RC-RES concealed sprinklers and LF concealed horizontal sidewall sprinklers.

Related applications

AquaSAFE™ Fire Safety Systems

Codes

Standards

Listings

Footnotes

Contact information

	Uponor Inc. 5925 148th Street West Apple Valley, MN 55124 T 800.321.4739 F 952.891.2008	Uponor Ltd. 6510 Kennedy Road Mississauga, ON L5T 2X4 T 888.594.7726 F 800.638.9517
--	---	---