For Residential and Commercial Applications				
Job Name		Engineer / Architect		
Job Location		Wholesaler		
Submittal Date		Contractor		

HUS11 Garden Hose Swivel Union – Female Hose Thread x Female Iron Pipe

Use: For use with residential and commercial grade garden hose. All female hose thread connections require a rubber washer (sold separately) inserted prior to installation


Operating Specifications:

Temperature: -35°- 100° F

Working Pressure: 75 psi maximum, intermittent to 150 psi

Standard

MATERIAL SPECIFICATIONS		
Fitting Body	C36000 brass	



Compliant

MATERIAL SPECIFICATIONS		
Fitting Body	Compliant brass	

Standard Part Listing:

HUS11-8-12	3/4" Female Hose Thread (swivel) x 1/2" Female Iron Pipe, rough brass
HUS11-12-12	3/4" Female Hose Thread (swivel) x 3/4" Female Iron Pipe, rough brass
HUS11-12-12 B	3/4" Female Hose Thread (swivel) x 3/4" Female Iron Pipe, rough brass, bulk

Compliant Part Listing:

HUS11-8-12X	3/4" Female Hose Thread (swivel) x 1/2" Female Iron Pipe, rough brass
HUS11-8-12X B	3/4" Female Hose Thread (swivel) x 1/2" Female Iron Pipe, rough brass, bulk
HUS11-12-12X	3/4" Female Hose Thread (swivel) x 3/4" Female Iron Pipe, rough brass
HUS11-12-12X B	3/4" Female Hose Thread (swivel) x 3/4" Female Iron Pipe, rough brass, bulk

PART DIMENSIONS (Inches)				
Model	DIA. A	НЕХ В	DIM. C	
HUS11-8-12	.578	7/8	1.20	
HUS11-12-12	.578	1-1/8	1.20	

Listings & Certifications:

 Compliant product CSA approved to California Health & Safety Code 116875 and Vermont Bill S.152 (Project # 2174785)



This specification and all information contained herein is the confidential and exclusive property of BrassCraft Manufacturing, and shall not be disclosed to others without the written consent of BrassCraft. This specification must be returned to BrassCraft if requested.

