



**SVC compression adapter**

- Only for type L copper, type K copper, type M copper
- Brass
- SVC
- Allows compression copper connection with SVC manifold without soldering

components

Brass nut, plastic insert

**Model 9438.5SV**

d	SVC	Wt [lb]	Quantity	Part No	DG
1/2	✓	0.086	10	<b>19305</b>	4
3/4	✓	0.320	10	<b>19306</b>	4



**SVC adapter**

- Bronze
- Male pipe thread, SVC

**Model 1022.6SV**

MPT	SVC	Wt [lb]	Quantity	Part No	DG
1/2	✓	0.140	5	<b>19109</b>	4
3/4	✓	0.165	5	<b>19110</b>	4



**Coupling**

- Bronze
- SVC

**Model 1022.7SV**

SVC1	SVC2	Wt [lb]	Quantity	Part No	DG
✓	✓	0.154	10	<b>19012</b>	4



**Strap-on temperature gauge set**

- Can be soldered

components

Gauge, mounting spring, heat transfer paste

**Model 2810.3US**

d	Temp. [°F]	Wt [lb]	Quantity	Part No	DG
2 1/2	32–250	0.240	1	<b>15055</b>	4



**Manifold**

- Equipped with shutoff / balancing valve Model 2834.7US
- Type L copper
- Solder inlet connection, PEX Press outlet connection

components

Brass valves

**Model 2834.9US**

Outlet(s)	d	P	gpm	Wt [lb]	Quantity	Part No	DG
12	1 1/2	5/8	32	13.851	1	<b>17223</b>	4
12	1 1/2	3/4	32	13.651	1	<b>17224</b>	4
12	2	5/8	45	16.295	1	<b>17204</b>	4
12	2	3/4	45	15.716	1	<b>17205</b>	4



**Manifold**

- Equipped with shutoff valve Model 2834.6US
- Type L copper
- Solder inlet connection, PEX Press outlet connection

components

Brass valves

**Model 2834.8US**

Outlet(s)	d	P	gpm	Wt [lb]	Quantity	Part No	DG
12	1 1/2	5/8	32	10.257	1	<b>17221</b>	4
12	1 1/2	3/4	32	10.027	1	<b>17222</b>	4
12	2	5/8	45	12.496	1	<b>17202</b>	4
12	2	3/4	45	11.917	1	<b>17203</b>	4