



AQUA JET O.D. DR - 13.5

SIZE	O.D	MINIMUM WALL	Weight per 100'	PSI RATING
3/4"	1.050	0.078	11.0	160
1"	1.315	0.097	16.8	160
1-1/4"	1.660	0.123	26.4	160
1-1/2"	1.900	0.141	34.4	160
2"	2.375	0.176	53.0	160
3"	3.500	0.259	115.2	160
4"	4.500	0.333	190.4	160
6"	6.625	0.491	413.3	160

AQUA JET O.D. DR - 11

SIZE	O.D	MINIMUM WALL	Weight per 100'	PSI RATING
3/4"	1.050	0.095	11.6	200
1"	1.315	0.120	18.3	200
1-1/4"	1.660	0.151	27.9	200
1-1/2"	1.900	0.173	38.3	200
2"	2.375	0.216	59.7	200
3"	3.500	0.318	129.0	200
4"	4.500	0.409	208.0	200
6"	6.625	0.602	496.8	200



AQUA JET O.D. DR - 9

SIZE	O.D	MINIMUM WALL	Weight per 100'	PSI RATING
3/4"	1.050	0.117	14.6	250
1"	1.315	0.146	23.0	250
1-1/4"	1.660	0.184	34.0	250
1-1/2"	1.900	0.211	48.0	250
2"	2.375	0.264	75.0	250
3"	3.500	0.389	160.0	250
4"	4.500	0.500	273.7	250
6"	6.625	0.736	593.0	250



SIDR-15 125 PSI

SIZE	I.D.	MINIMUM WALL	WEIGHT PER 100"	MAX PSI AT 73.4°F	COIL LENGTH
3/4"	0.824	0.060	7.4	125	100/400
1"	1.049	0.070	10.6	125	100/300
1-1/4"	1.380	0.0892	18.5	125	100/300
1-1/2"	1.610	0.107	25.1	125	100/250
2"	2.067	0.138	41.1	125	100/250
3"	3.068	0.205	89.5	125	100/200

SIDR-11.5 160 PSI

SIZE	I.D.	MINIMUM WALL	WEIGHT PER 100"	MAX PSI AT 73.4°F	COIL LENGTH
1/2"	0.622	0.060	5.8	160	100/400
3/4"	0.824	0.072	9.0	160	100/400
1"	1.049	0.091	14.2	160	100/250
1-1/4"	1.380	0.120	24.5	160	100/250
1-1/2"	1.610	0.140	33.1	160	100/200
2"	2.067	0.180	54.2	160	100/200

SIDR-9 200 PSI

SIZE	I.D.	MINIMUM WALL	WEIGHT PER 100"	MAX PSI AT 73.4°F	COIL LENGTH
3/4"	0.824	0.092	11.5	200	100/400
1"	1.049	0.117	18.5	200	SEE NOTE
1-1/4"	1.380	0.153	31.5	200	100/300
1-1/2"	1.610	0.179	43.0	200	100/250
2"	2.067	0.230	70.4	200	100/200



SDR-7 250 PSI

SIZE	I.D.	MINIMUM WALL	WEIGHT PER 100"	MAX PSI AT 73.4°F	COIL LENGTH
3/4"	0.824	0.118	15.2	250	100/400
1"	1.049	0.150	24.3	250	SEE NOTE
1-1/4"	1.380	0.197	41.6	250	100/300
1-1/2"	1.610	0.230	56.4	250	100/250
2"	2.067	0.295	92.4	250	100/200

SDR-9 AQUA JET

SIZE	NOMINAL O.D.	NOMINAL I.D.	MINIMUM WALL	WEIGHT PER 100"	COIL LENGTH
3/4"	0.875	0.671	0.097	10.3	100/500
1"	1.125	0.865	0.125	16.8	100/500
1-1/4"	1.375	1.060	0.153	25.0	100/300
1-1/2"	1.625	1.253	0.181	35.0	100/300
2"	2.125	1.637	0.236	59.7	100/300