

Product Features

- Operating Temperature: 32°F-176°F
- Operating Pressure: 180 PSI
- Burst Pressure: 1200 PSI
- Hose Brabs: Low Lead Brass
- Washers: Rubber
- Nut: Heavy Duty Nickel Plated Brass
- Inner Hose: Heavy Duty Reinforced PVC
- Outer Wire Braid: 304 Stainless Steel Wire
- Ferrules: Brass



4PRO38.12.COMPF12BLS

Model Numbers

4PRO38.12.COMPF12BLS
 4PRO38.12.COMPF16BLS
 4PRO38.12.COMPF20BLS
 4PRO38.12.COMPF30BLS
 4PRO38.12.COMP12BLS
 4PRO38.38COMP12BLS
 4PRO38.38COMP20BLS
 4PRO38.12COMP20BLS

3/8" Comp x 1/2" FIP x 12" SS Braided Lav Supply
 3/8" Comp x 1/2" FIP x 16" SS Braided Lav Supply
 3/8" Comp x 1/2" FIP x 20" SS Braided Lav Supply
 3/8" Comp x 1/2" FIP x 30" SS Braided Lav Supply
 3/8" Comp x 1/2" Comp x 12" SS Braided Lav Supply
 3/8" Comp x 3/8" Comp x 12" SS Braided Lav Supply
 3/8" Comp x 3/8" Comp x 20" SS Braided Lav Supply
 3/8" Comp x 1/2" Comp x 20" SS Braided Lav Supply

| | |
|--------------------|--|
| Job Name | |
| Date | |
| Model Specified | |
| Quantity | |
| Customer | |
| Contractor | |
| Architect/engineer | |