

## Features

- Elongated bowl offers added room and comfort.
- Standard height.
- 2-1/8" (54 mm) fully-glazed trapway.
- Combines with 402362, 402362-RA, 402363, 402363-RA tanks to make a complete 402321, 402321-RA, 402324, 402324-RA toilet.

## Installation

- Pro Force<sup>®</sup> Plus flushing technology delivers greater flushing power than previous Pro Force<sup>®</sup> models.
- Three-bolt quick-connect installation.
- Standard 12" (305 mm) rough-in.
- Seat and supply line sold separately.

## **Recommended Products/Accessories**

402362 Toilet tank 402362-RA Toilet tank 402363 Toilet tank 402363-RA Toilet tank K-23726 Drain treatment K-23724 Toilet cleaner & disinfectant K-23734 Toilet bowl cleaner & disinfectant



Windham<sup>™</sup>

403217

Elongated toilet bowl

### Codes/Standards ASME A112.19.2/CSA B45.1

# STERLING<sup>®</sup> Warranty - Toilets and Lavatories

See website for detailed warranty information.

## **Available Colors/Finishes**

Color tiles intended for reference only.

### Color Code Description

| 0  | White          |
|----|----------------|
| 96 | KOHLER Biscuit |



No image available. This product is a component and not intended to be a standalone installation.

## **Technical Information**

| All product dimensions are nominal. |                               |  |  |
|-------------------------------------|-------------------------------|--|--|
| Toilet type:                        | Two-piece, Floor-mount        |  |  |
| Waste Outlet:                       | Floor                         |  |  |
| Bowl shape:                         | Elongated                     |  |  |
| Trap passageway:                    | 2-1/8" (54 mm)                |  |  |
| Water surface size:                 | 9-3/4" x 7" (248 mm x 178 mm) |  |  |
| Rim to water surface:               | 6-1/2" (165 mm)               |  |  |
| Rough-in:                           | 12" (305 mm)                  |  |  |
| Seat-mounting holes:                | 5-1/2" (140 mm)               |  |  |
|                                     |                               |  |  |

### Notes

Install this product according to the installation instructions.